# Package 'gert'

January 12, 2026

**Type** Package

**Title** Simple Git Client for R

**Version** 2.3.1

**Description** Simple git client for R based on 'libgit2' <https://libgit2.org> with support for SSH and HTTPS remotes. All functions in 'gert' use basic R data types (such as vectors and data-frames) for their arguments and return values. User credentials are shared with command line 'git' through the git-credential store and ssh keys stored on disk or ssh-agent.

**License** MIT + file LICENSE

**URL** https://docs.ropensci.org/gert/,
https://ropensci.r-universe.dev/gert

**BugReports** https://github.com/r-lib/gert/issues

**Imports** askpass, credentials (>= 1.2.1), openssl (>= 2.0.3), rstudioapi (>= 0.11), sys, zip (>= 2.1.0)

**Suggests** spelling, knitr, rmarkdown, testthat

**VignetteBuilder** knitr

**Encoding** UTF-8

**RoxygenNote** 7.3.3

**SystemRequirements** libgit2 (>= 1.0): libgit2-devel (rpm) or libgit2-dev (deb)

**Language** en-US

**NeedsCompilation** yes

**Author** Jeroen Ooms [aut, cre] (ORCID: <https://orcid.org/0000-0002-4035-0289>), Jennifer Bryan [ctb] (ORCID: <https://orcid.org/0000-0002-6983-2759>)

**Maintainer** Jeroen Ooms <jeroenooms@gmail.com>

**Repository** CRAN

**Date/Publication** 2026-01-11 23:50:02 UTC

# Contents


git_archive . . . 2
git_branch . . . 3
git_checkout_pull_request . . . 4
git_commit . . . 5
git_config . . . 7
git_diff . . . 9
git_fetch . . . 9
git_ignore . . . 12
git_merge . . . 13
git_open . . . 14
git_rebase . . . 15
git_remote . . . 16
git_repo . . . 17
git_reset . . . 18
git_signature . . . 19
git_stash . . . 20
git_submodule_list . . . 21
git_tag . . . 22
git_worktree . . . 22
libgit2_config . . . 25
user_is_configured . . . 26

**Index** **27**


---

`git_archive` *Git Archive*

---

## Description

Exports the files in your repository to a zip file that is returned by the function.

## Usage

```
git_archive_zip(file = NULL, repo = ".")
```

## Arguments

| | |
|---|---|
| `file` | name of the output zip file. Default is returned by the function |
| `repo` | The path to the git repository. If the directory is not a repository, parent directories are considered (see git_find). To disable this search, provide the filepath protected with `I()`. When using this parameter, always explicitly call by name (i.e. `repo = `) because future versions of gert may have additional parameters. |

## Value

path to the zip file that was created

## See Also

Other git: git_branch(), git_commit(), git_config(), git_diff(), git_fetch(), git_ignore, git_merge(), git_rebase(), git_remote, git_repo, git_reset(), git_signature(), git_stash, git_tag, git_worktree

---

`git_branch` *Git Branch*

---

## Description

Create, list, and checkout branches.

## Usage

```
git_branch(repo = ".")

git_branch_list(local = NULL, repo = ".")

git_branch_checkout(branch, force = FALSE, orphan = FALSE, repo = ".")

git_branch_create(
  branch,
  ref = "HEAD",
  checkout = TRUE,
  force = FALSE,
  repo = "."
)

git_branch_delete(branch, repo = ".")

git_branch_move(branch, new_branch, force = FALSE, repo = ".")

git_branch_fast_forward(ref, repo = ".")

git_branch_set_upstream(upstream, branch = git_branch(repo), repo = ".")

git_branch_exists(branch, local = TRUE, repo = ".")
```

## Arguments

| | |
|---|---|
| `repo` | The path to the git repository. If the directory is not a repository, parent directories are considered (see git_find). To disable this search, provide the filepath protected with `I()`. When using this parameter, always explicitly call by name (i.e. `repo = `) because future versions of gert may have additional parameters. |
| `local` | set TRUE to only check for local branches, FALSE to check for remote branches. Use NULL to return all branches. |

| | |
|---|---|
| branch | name of branch to check out |
| force | overwrite existing branch |
| orphan | if branch does not exist, checkout unborn branch |
| ref | string with a branch/tag/commit |
| checkout | move HEAD to the newly created branch |
| new_branch | target name of the branch once the move is performed; this name is validated for consistency. |
| upstream | remote branch from git_branch_list, for example "origin/master" |

## See Also

Other git: git_archive, git_commit(), git_config(), git_diff(), git_fetch(), git_ignore, git_merge(), git_rebase(), git_remote, git_repo, git_reset(), git_signature(), git_stash, git_tag, git_worktree

---

# git_checkout_pull_request

*GitHub Wrappers*

---

## Description

Fetch and checkout pull requests.

## Usage

```
git_checkout_pull_request(pr = 1, remote = NULL, repo = ".")

git_fetch_pull_requests(pr = "*", remote = NULL, repo = ".")
```

## Arguments

| | |
|---|---|
| pr | number with PR to fetch or check out. Use "*" to fetch all pull requests. |
| remote | Optional. Name of a remote listed in git_remote_list(). If unspecified and the current branch is already tracking branch a remote branch, that remote is honored. Otherwise, defaults to origin. |
| repo | The path to the git repository. If the directory is not a repository, parent directories are considered (see git_find). To disable this search, provide the filepath protected with I(). When using this parameter, always explicitly call by name (i.e. repo = ) because future versions of gert may have additional parameters. |

## Details

By default git_fetch_pull_requests will download all PR branches. To remove these again simply use git_fetch(prune = TRUE).

`git_commit` *Stage and commit changes*

## Description

To commit changes, start by *staging* the files to be included in the commit using `git_add()` or `git_rm()`. Use `git_status()` to see an overview of staged and unstaged changes, and finally `git_commit()` creates a new commit with currently staged files.

`git_commit_all()` is a convenience function that automatically stages and commits all modified files. Note that `git_commit_all()` does **not** add new, untracked files to the repository. You need to make an explicit call to `git_add()` to start tracking new files.

`git_log()` shows the most recent commits and `git_ls()` lists all the files that are being tracked in the repository. `git_stat_files()`

## Usage

```
git_commit(message, author = NULL, committer = NULL, repo = ".")

git_commit_all(message, author = NULL, committer = NULL, repo = ".")

git_commit_info(ref = "HEAD", repo = ".")

git_commit_id(ref = "HEAD", repo = ".")

git_commit_stats(ref = "HEAD", repo = ".")

git_commit_descendant_of(ancestor, ref = "HEAD", repo = ".")

git_add(files, force = FALSE, repo = ".")

git_rm(files, repo = ".")

git_status(staged = NULL, pathspec = NULL, repo = ".")

git_conflicts(repo = ".")

git_ls(repo = ".", ref = NULL)

git_log(ref = "HEAD", max = 100, after = NULL, repo = ".")

git_stat_files(files, ref = "HEAD", max = NULL, repo = ".")
```

## Arguments

| | |
|---|---|
| `message` | a commit message |
| `author` | A git_signature value, default is `git_signature_default()`. |

| | |
|---|---|
| committer | A git_signature value, default is same as author |
| repo | The path to the git repository. If the directory is not a repository, parent directories are considered (see git_find). To disable this search, provide the filepath protected with I(). When using this parameter, always explicitly call by name (i.e. repo = ) because future versions of gert may have additional parameters. |
| ref | revision string with a branch/tag/commit value |
| ancestor | a reference to a potential ancestor commit |
| files | vector of paths relative to the git root directory. Use "." to stage all changed files. |
| force | add files even if in gitignore |
| staged | return only staged (TRUE) or unstaged files (FALSE). Use NULL or NA to show both (default). |
| pathspec | character vector with paths to match |
| max | lookup at most latest n parent commits |
| after | date or timestamp: only include commits starting this date |

## Value

- git_status(), git_ls(): A data frame with one row per file
- git_log(): A data frame with one row per commit
- git_commit(), git_commit_all(): A SHA

## See Also

Other git: git_archive, git_branch(), git_config(), git_diff(), git_fetch(), git_ignore, git_merge(), git_rebase(), git_remote, git_repo, git_reset(), git_signature(), git_stash, git_tag, git_worktree

## Examples

```
oldwd <- getwd()
repo <- file.path(tempdir(), "myrepo")
git_init(repo)
setwd(repo)

# Set a user if no default
if(!user_is_configured()){
  git_config_set("user.name", "Jerry")
  git_config_set("user.email", "jerry@gmail.com")
}

writeLines(letters[1:6], "alphabet.txt")
git_status()

git_add("alphabet.txt")
git_status()
```

```
git_commit("Start alphabet file")
git_status()

git_ls()

git_log()

cat(letters[7:9], file = "alphabet.txt", sep = "\n", append = TRUE)
git_status()

git_commit_all("Add more letters")

# cleanup
setwd(oldwd)
unlink(repo, recursive = TRUE)
```

---

`git_config` *Get or set Git configuration*

---

## Description

Get or set Git options, as `git config` does on the command line. **Global** settings affect all of a user's Git operations (`git config --global`), whereas **local** settings are scoped to a specific repository (`git config --local`). When both exist, local options always win. Four functions address the four possible combinations of getting vs setting and global vs. local.

| | **local** | **global** |
|---|---|---|
| get | `git_config()` | `git_config_global()` |
| set | `git_config_set()` | `git_config_global_set()` |

## Usage

```
git_config(repo = ".")

git_config_global()

git_config_set(name, value, repo = ".")

git_config_global_set(name, value)
```

## Arguments

| | |
|---|---|
| `repo` | The path to the git repository. If the directory is not a repository, parent directories are considered (see git_find). To disable this search, provide the filepath protected with `I()`. When using this parameter, always explicitly call by name (i.e. `repo = `) because future versions of gert may have additional parameters. |
| `name` | Name of the option to set |
| `value` | Value to set. Must be a string, logical, number or `NULL` (to unset). |

## Value

- `git_config()`: a `data.frame` of the Git options "in force" in the context of `repo`, one row per option. The `level` column reveals whether the option is determined from global or local config.
- `git_config_global()`: a `data.frame`, as for `git_config()`, except only for global Git options.
- `git_config_set()`, `git_config_global_set()`: The previous value of `name` in local or global config, respectively. If this option was previously unset, returns `NULL`. Returns invisibly.

## Note

All entries in the `name` column are automatically normalised to lowercase (see https://libgit2.org/libgit2/#HEAD/type/git_config_entry for details).

## See Also

Other git: `git_archive`, `git_branch()`, `git_commit()`, `git_diff()`, `git_fetch()`, `git_ignore`, `git_merge()`, `git_rebase()`, `git_remote`, `git_repo`, `git_reset()`, `git_signature()`, `git_stash`, `git_tag`, `git_worktree`

## Examples

```
# Set and inspect a local, custom Git option
r <- file.path(tempdir(), "gert-demo")
git_init(r)

previous <- git_config_set("aaa.bbb", "ccc", repo = r)
previous
cfg <- git_config(repo = r)
subset(cfg, level == "local")
cfg$value[cfg$name == "aaa.bbb"]

previous <- git_config_set("aaa.bbb", NULL, repo = r)
previous
cfg <- git_config(repo = r)
subset(cfg, level == "local")
cfg$value[cfg$name == "aaa.bbb"]

unlink(r, recursive = TRUE)

## Not run:
# Set global Git options
git_config_global_set("user.name", "Your Name")
git_config_global_set("user.email", "your@email.com")
git_config_global()

## End(Not run)
```

## git_diff *Git Diff*

### Description

View changes in a commit or in the current working directory.

### Usage

```
git_diff(ref = NULL, repo = ".")

git_diff_patch(ref = NULL, repo = ".")
```

### Arguments

| | |
|---|---|
| ref | a reference such as "HEAD", or a commit id, or NULL to the diff the working directory against the repository index. |
| repo | The path to the git repository. If the directory is not a repository, parent directories are considered (see git_find). To disable this search, provide the filepath protected with I(). When using this parameter, always explicitly call by name (i.e. repo = ) because future versions of gert may have additional parameters. |

### See Also

Other git: git_archive, git_branch(), git_commit(), git_config(), git_fetch(), git_ignore, git_merge(), git_rebase(), git_remote, git_repo, git_reset(), git_signature(), git_stash, git_tag, git_worktree

## git_fetch *Push and pull*

### Description

Functions to connect with a git server (remote) to fetch or push changes. The 'credentials' package is used to handle authentication, the credentials vignette explains the various authentication methods for SSH and HTTPS remotes.

### Usage

```
git_fetch(
  remote = NULL,
  refspec = NULL,
  password = askpass,
  ssh_key = NULL,
  prune = FALSE,
```

```
  verbose = interactive(),
  repo = "."
)

git_remote_ls(
  remote = NULL,
  password = askpass,
  ssh_key = NULL,
  verbose = interactive(),
  repo = "."
)

git_push(
  remote = NULL,
  refspec = NULL,
  set_upstream = NULL,
  password = askpass,
  ssh_key = NULL,
  mirror = FALSE,
  force = FALSE,
  verbose = interactive(),
  repo = "."
)

git_clone(
  url,
  path = NULL,
  branch = NULL,
  password = askpass,
  ssh_key = NULL,
  bare = FALSE,
  mirror = FALSE,
  verbose = interactive()
)

git_pull(remote = NULL, rebase = FALSE, ..., repo = ".")
```

## Arguments

| | |
|---|---|
| remote | Optional. Name of a remote listed in `git_remote_list()`. If unspecified and the current branch is already tracking branch a remote branch, that remote is honored. Otherwise, defaults to `origin`. |
| refspec | string with mapping between remote and local refs. Default uses the default refspec from the remote, which usually fetches all branches. |
| password | a string or a callback function to get passwords for authentication or password protected ssh keys. Defaults to askpass which checks `getOption('askpass')`. |
| ssh_key | path or object containing your ssh private key. By default we look for keys in `ssh-agent` and credentials::ssh_key_info. |

| | |
|---|---|
| prune | delete tracking branches that no longer exist on the remote, or are not in the refspec (such as pull requests). |
| verbose | display some progress info while downloading |
| repo | The path to the git repository. If the directory is not a repository, parent directories are considered (see git_find). To disable this search, provide the filepath protected with I(). When using this parameter, always explicitly call by name (i.e. repo = ) because future versions of gert may have additional parameters. |
| set_upstream | change the branch default upstream to remote. If NULL, this will set the branch upstream only if the push was successful and if the branch does not have an upstream set yet. |
| mirror | use the --mirror flag |
| force | use the --force flag |
| url | remote url. Typically starts with https://github.com/ for public repositories, and https://yourname@github.com/ or git@github.com/ for private repos. You will be prompted for a password or pat when needed. |
| path | Directory of the Git repository to create. |
| branch | name of branch to check out locally |
| bare | use the --bare flag |
| rebase | if TRUE we try to rebase instead of merge local changes. This is not possible in case of conflicts (you will get an error). |
| ... | arguments passed to git_fetch |

## Details

Use git_fetch() and git_push() to sync a local branch with a remote branch. Here git_pull() is a wrapper for git_fetch() which then tries to fast-forward the local branch after fetching.

## See Also

Other git: git_archive, git_branch(), git_commit(), git_config(), git_diff(), git_ignore, git_merge(), git_rebase(), git_remote, git_repo, git_reset(), git_signature(), git_stash, git_tag, git_worktree

## Examples

```
{# Clone a small repository
git_dir <- file.path(tempdir(), 'antiword')
git_clone('https://github.com/ropensci/antiword', git_dir)

# Change into the repo directory
olddir <- getwd()
setwd(git_dir)

# Show some stuff
git_log()
git_branch_list()
git_remote_list()
```

```
# Add a file
write.csv(iris, 'iris.csv')
git_add('iris.csv')

# Commit the change
jerry <- git_signature("Jerry", "jerry@hotmail.com")
git_commit('added the iris file', author = jerry)

# Now in the log:
git_log()

# Cleanup
setwd(olddir)
unlink(git_dir, recursive = TRUE)
}
```

---

`git_ignore` *Git Ignore*

---

## Description

Test if files would be ignored by `.gitignore` rules

## Usage

```
git_ignore_path_is_ignored(path, repo = ".")
```

## Arguments

| | |
|---|---|
| `path` | A character vector of paths to test within the repo |
| `repo` | The path to the git repository. If the directory is not a repository, parent directories are considered (see git_find). To disable this search, provide the filepath protected with `I()`. When using this parameter, always explicitly call by name (i.e. `repo = `) because future versions of gert may have additional parameters. |

## Value

A logical vector the same length as `path`, indicating if the paths would be ignored.

## See Also

Other git: `git_archive`, `git_branch()`, `git_commit()`, `git_config()`, `git_diff()`, `git_fetch()`, `git_merge()`, `git_rebase()`, `git_remote`, `git_repo`, `git_reset()`, `git_signature()`, `git_stash`, `git_tag`, `git_worktree`

git_merge *Merging tools*

## Description

Use git_merge to merge a branch into the current head. Based on how the branches have diverged, the function will select a fast-forward or merge-commit strategy.

## Usage

```
git_merge(ref, commit = TRUE, squash = FALSE, repo = ".")

git_merge_stage_only(ref, squash = FALSE, repo = ".")

git_merge_find_base(ref, target = "HEAD", repo = ".")

git_merge_analysis(ref, repo = ".")

git_merge_abort(repo = ".")
```

## Arguments

| | |
|---|---|
| ref | branch or commit that you want to merge |
| commit | automatically create a merge commit if the merge succeeds without conflicts. Set this to FALSE if you want to customize your commit message/author. |
| squash | omits the second parent from the commit, which make the merge a regular single-parent commit. |
| repo | The path to the git repository. If the directory is not a repository, parent directories are considered (see git_find). To disable this search, provide the filepath protected with I(). When using this parameter, always explicitly call by name (i.e. repo = ) because future versions of gert may have additional parameters. |
| target | the branch where you want to merge into. Defaults to current HEAD. |

## Details

By default git_merge automatically commits the merge commit upon success. However if the merge fails with merge-conflicts, or if commit is set to FALSE, the changes are staged and the repository is put in merging state, and you have to manually run git_commit or git_merge_abort to proceed.

Other functions are more low-level tools that are used by git_merge. git_merge_find_base looks up the commit where two branches have diverged (i.e. the youngest common ancestor). The git_merge_analysis is used to test if a merge can simply be fast forwarded or not.

The git_merge_stage_only function applies and stages changes, without committing or fast-forwarding.

## See Also

Other git: git_archive, git_branch(), git_commit(), git_config(), git_diff(), git_fetch(), git_ignore, git_rebase(), git_remote, git_repo, git_reset(), git_signature(), git_stash, git_tag, git_worktree

---

`git_open` *Open local repository*

---

## Description

Returns a pointer to a libgit2 repository object.This function is mainly for internal use; users should simply reference a repository in gert by by the path to the directory.

## Usage

```
git_open(repo = ".")
```

## Arguments

| | |
|---|---|
| `repo` | The path to the git repository. If the directory is not a repository, parent directories are considered (see git_find). To disable this search, provide the filepath protected with `I()`. When using this parameter, always explicitly call by name (i.e. `repo = `) because future versions of gert may have additional parameters. |

## Value

an pointer to the libgit2 repository

## Examples

```
r <- tempfile(pattern = "gert")
git_init(r)
r_ptr <- git_open(r)
r_ptr
git_open(r_ptr)
git_info(r)

# cleanup
unlink(r, recursive = TRUE)
```

`git_rebase` *Cherry-Pick and Rebase*

## Description

A cherry-pick applies the changes from a given commit (from another branch) onto the current branch. A rebase resets the branch to the state of another branch (upstream) and then re-applies your local changes by cherry-picking each of your local commits onto the upstream commit history.

## Usage

```
git_rebase_list(upstream = NULL, repo = ".")

git_rebase_commit(upstream = NULL, repo = ".")

git_cherry_pick(commit, repo = ".")

git_ahead_behind(upstream = NULL, ref = "HEAD", repo = ".")
```

## Arguments

| | |
|---|---|
| `upstream` | branch to which you want to rewind and re-apply your local commits. The default uses the remote upstream branch with the current state on the git server, simulating git_pull. |
| `repo` | The path to the git repository. If the directory is not a repository, parent directories are considered (see git_find). To disable this search, provide the filepath protected with `I()`. When using this parameter, always explicitly call by name (i.e. `repo = `) because future versions of gert may have additional parameters. |
| `commit` | id of the commit to cherry pick |
| `ref` | string with a branch/tag/commit |

## Details

`git_rebase_list` shows your local commits that are missing from the `upstream` history, and if they conflict with upstream changes. It does so by performing a rebase dry-run, without committing anything. If there are no conflicts, you can use `git_rebase_commit` to rewind and rebase your branch onto `upstream`. Gert only support a clean rebase; it never leaves the repository in unfinished "rebasing" state. If conflicts arise, `git_rebase_commit` will raise an error without making changes.

## See Also

Other git: `git_archive`, `git_branch()`, `git_commit()`, `git_config()`, `git_diff()`, `git_fetch()`, `git_ignore`, `git_merge()`, `git_remote`, `git_repo`, `git_reset()`, `git_signature()`, `git_stash`, `git_tag`, `git_worktree`

`git_remote` *Git Remotes*

## Description

List, add, configure, or remove remotes.

## Usage

```
git_remote_list(repo = ".")

git_remote_add(url, name = "origin", refspec = NULL, repo = ".")

git_remote_remove(remote, repo = ".")

git_remote_info(remote = NULL, repo = ".")

git_remote_set_url(url, remote = NULL, repo = ".")

git_remote_set_pushurl(url, remote = NULL, repo = ".")

git_remote_refspecs(remote = NULL, repo = ".")
```

## Arguments

| | |
|---|---|
| `repo` | The path to the git repository. If the directory is not a repository, parent directories are considered (see git_find). To disable this search, provide the filepath protected with `I()`. When using this parameter, always explicitly call by name (i.e. `repo = `) because future versions of gert may have additional parameters. |
| `url` | server url (https or ssh) |
| `name` | unique name for the new remote |
| `refspec` | optional string with the remote fetch value |
| `remote` | name of an existing remote. Default `NULL` means the remote from the upstream of the current branch. |

## See Also

Other git: `git_archive`, `git_branch()`, `git_commit()`, `git_config()`, `git_diff()`, `git_fetch()`, `git_ignore`, `git_merge()`, `git_rebase()`, `git_repo`, `git_reset()`, `git_signature()`, `git_stash`, `git_tag`, `git_worktree`

`git_repo` *Create or discover a local Git repository*

## Description

Use `git_init()` to create a new repository or `git_find()` to discover an existing local repository. `git_info()` shows basic information about a repository, such as the SHA and branch of the current HEAD.

## Usage

```
git_init(path = ".", bare = FALSE)

git_find(path = ".")

git_info(repo = ".")
```

## Arguments

| | |
|---|---|
| `path` | the location of the git repository, see details. |
| `bare` | if true, a Git repository without a working directory is created |
| `repo` | The path to the git repository. If the directory is not a repository, parent directories are considered (see git_find). To disable this search, provide the filepath protected with `I()`. When using this parameter, always explicitly call by name (i.e. `repo = `) because future versions of gert may have additional parameters. |

## Details

For `git_init()` the `path` parameter sets the directory of the git repository to create. If this directory already exists, it must be empty. If it does not exist, it is created, along with any intermediate directories that don't yet exist. For `git_find()` the `path` arguments specifies the directory at which to start the search for a git repository. If it is not a git repository itself, then its parent directory is consulted, then the parent's parent, and so on.

## Value

The path to the Git repository.

## See Also

Other git: `git_archive`, `git_branch()`, `git_commit()`, `git_config()`, `git_diff()`, `git_fetch()`, `git_ignore`, `git_merge()`, `git_rebase()`, `git_remote`, `git_reset()`, `git_signature()`, `git_stash`, `git_tag`, `git_worktree`

## Examples

```
# directory does not yet exist
r <- tempfile(pattern = "gert")
git_init(r)
git_find(r)

# create a child directory, then a grandchild, then search
r_grandchild_dir <- file.path(r, "aaa", "bbb")
dir.create(r_grandchild_dir, recursive = TRUE)
git_find(r_grandchild_dir)

# cleanup
unlink(r, recursive = TRUE)

# directory exists but is empty
r <- tempfile(pattern = "gert")
dir.create(r)
git_init(r)
git_find(r)

# cleanup
unlink(r, recursive = TRUE)
```

---

# git_reset *Reset your repo to a previous state*

---

## Description

- `git_reset_hard()` resets the index and working tree
- `git_reset_soft()` does not touch the index file or the working tree
- `git_reset_mixed()` resets the index but not the working tree.

## Usage

```
git_reset_hard(ref = "HEAD", repo = ".")

git_reset_soft(ref = "HEAD", repo = ".")

git_reset_mixed(ref = "HEAD", repo = ".")
```

## Arguments

| | |
|---|---|
| `ref` | string with a branch/tag/commit |
| `repo` | The path to the git repository. If the directory is not a repository, parent directories are considered (see git_find). To disable this search, provide the filepath protected with `I()`. When using this parameter, always explicitly call by name (i.e. `repo = `) because future versions of gert may have additional parameters. |

## See Also

Other git: git_archive, git_branch(), git_commit(), git_config(), git_diff(), git_fetch(), git_ignore, git_merge(), git_rebase(), git_remote, git_repo, git_signature(), git_stash, git_tag, git_worktree

---

`git_signature` *Author Signature*

---

## Description

A signature contains the author and timestamp of a commit. Each commit includes a signature of the author and committer (which can be identical).

## Usage

```
git_signature_default(repo = ".")

git_signature(name, email, time = NULL)

git_signature_parse(sig)
```

## Arguments

| | |
|---|---|
| repo | The path to the git repository. If the directory is not a repository, parent directories are considered (see git_find). To disable this search, provide the filepath protected with I(). When using this parameter, always explicitly call by name (i.e. repo = ) because future versions of gert may have additional parameters. |
| name | Real name of the committer |
| email | Email address of the committer |
| time | timestamp of class POSIXt or NULL |
| sig | string in proper "First Last <your@email.com>" format, see details. |

## Details

A signature string has format "Real Name <email> timestamp tzoffset". The timestamp tzoffset piece can be omitted in which case the current local time is used. If not omitted, timestamp must contain the number of seconds since the Unix epoch and tzoffset is the timezone offset in hhmm format (note the lack of a colon separator)

## See Also

Other git: git_archive, git_branch(), git_commit(), git_config(), git_diff(), git_fetch(), git_ignore, git_merge(), git_rebase(), git_remote, git_repo, git_reset(), git_stash, git_tag, git_worktree

## Examples

```
# Your default user
try(git_signature_default())

# Specify explicit name and email
git_signature("Some committer", "sarah@gmail.com")

# Create signature for an hour ago
(sig <- git_signature("Han", "han@company.com", Sys.time() - 3600))

# Parse a signature
git_signature_parse(sig)
git_signature_parse("Emma <emma@mu.edu>")
```

---

# git_stash *Stashing changes*

---

## Description

Temporary stash away changed from the working directory.

## Usage

```
git_stash_save(
  message = "",
  keep_index = FALSE,
  include_untracked = FALSE,
  include_ignored = FALSE,
  repo = "."
)

git_stash_pop(index = 0, repo = ".")

git_stash_drop(index = 0, repo = ".")

git_stash_list(repo = ".")
```

## Arguments

| | |
|---|---|
| message | optional message to store the stash |
| keep_index | changes already added to the index are left intact in the working directory |
| include_untracked | untracked files are also stashed and then cleaned up from the working directory |
| include_ignored | ignored files are also stashed and then cleaned up from the working directory |

| | |
|---|---|
| repo | The path to the git repository. If the directory is not a repository, parent directories are considered (see git_find). To disable this search, provide the filepath protected with I(). When using this parameter, always explicitly call by name (i.e. repo = ) because future versions of gert may have additional parameters. |
| index | The position within the stash list. 0 points to the most recent stashed state. |

## See Also

Other git: git_archive, git_branch(), git_commit(), git_config(), git_diff(), git_fetch(), git_ignore, git_merge(), git_rebase(), git_remote, git_repo, git_reset(), git_signature(), git_tag, git_worktree

---

# git_submodule_list *Submodules*

---

## Description

Interact with submodules in the repository.

## Usage

```
git_submodule_list(repo = ".")

git_submodule_info(submodule, repo = ".")

git_submodule_init(submodule, overwrite = FALSE, repo = ".")

git_submodule_set_to(submodule, ref, checkout = TRUE, repo = ".")

git_submodule_add(url, path = basename(url), ref = "HEAD", ..., repo = ".")

git_submodule_fetch(submodule, ..., repo = ".")
```

## Arguments

| | |
|---|---|
| repo | The path to the git repository. If the directory is not a repository, parent directories are considered (see git_find). To disable this search, provide the filepath protected with I(). When using this parameter, always explicitly call by name (i.e. repo = ) because future versions of gert may have additional parameters. |
| submodule | name of the submodule |
| overwrite | overwrite existing entries |
| ref | a branch or tag or hash with |
| checkout | actually switch the contents of the directory to this commit |
| url | full git url of the submodule |
| path | relative of the submodule |
| ... | extra arguments for git_fetch for authentication things |

## git_tag *Git Tag*

### Description

Create and list tags.

### Usage

```
git_tag_list(match = "*", repo = ".")

git_tag_create(name, message, ref = "HEAD", repo = ".")

git_tag_delete(name, repo = ".")

git_tag_push(name, ..., repo = ".")
```

### Arguments

| | |
|---|---|
| match | pattern to filter tags (use * for wildcard) |
| repo | The path to the git repository. If the directory is not a repository, parent directories are considered (see git_find). To disable this search, provide the filepath protected with I(). When using this parameter, always explicitly call by name (i.e. repo = ) because future versions of gert may have additional parameters. |
| name | tag name |
| message | tag message |
| ref | target reference to tag |
| ... | other arguments passed to git_push |

### See Also

Other git: git_archive, git_branch(), git_commit(), git_config(), git_diff(), git_fetch(), git_ignore, git_merge(), git_rebase(), git_remote, git_repo, git_reset(), git_signature(), git_stash, git_worktree

## git_worktree *Git Worktrees*

## Description

Worktrees represent an alternative location to checkout a branch into. Rather than checking out a branch in your main working tree (which changes the branch you are currently on and forces you to stash any existing work), you can instead check that branch out into a separate *linked worktree* with its own working tree. Practically, a worktree is just a separate folder that a branch is checked out into, with some extra git metadata that links it back to the main working tree.

`git_worktree_list()` returns a data frame of information about the worktrees linked to the main working tree.

`git_worktree_exists()` lets you check whether or not a worktree by the name of `name` exists for this `repo`.

`git_worktree_path()` returns the file path to the worktree.

`git_worktree_add()` creates a new worktree called `name` in the folder pointed to by `path`, and checks `branch` out into it.

`git_worktree_remove()` removes a worktree. It does so by deleting the folder provided as the `path` to `git_worktree_add()`, and then cleaning up some git metadata in the main working tree that linked the main working tree to the removed worktree. The `branch` checked out by the worktree is not deleted. Note that this is just a wrapper around `git_worktree_prune()` that sets some desirable defaults for aggressive removal.

`git_worktree_prune()` is more cautious than `git_worktree_remove()`. It refuses to prune *valid* or *locked* worktrees by default, and also refuses the delete the working tree of the worktree by default (i.e. the folder at `path`). It is automatically run by git itself on periodic intervals to prune outdated worktrees. For interactive usage, you typically want `git_worktree_remove()` instead. `git_worktree_is_prunable()` lets you check if a worktree is prunable with the given options.

`git_worktree_lock()`, `git_worktree_unlock()`, and `git_worktree_is_locked()` help you manage whether or not a worktree is *locked*. When a worktree is locked, it is not automatically cleaned up by `git_worktree_prune()` (and git itself) on periodic intervals, even when it looks *invalid*. This is typically only useful when your worktree is on a hard drive that isn't always connected (which can make it look *invalid* when disconnected, typically making it a candidate for automatic pruning).

`git_worktree_is_valid()` checks whether a worktree is valid or not. A *valid* worktree requires both the git data structures inside the main working tree and this worktree to be present.

## Usage

```
git_worktree_list(repo = ".")

git_worktree_exists(name, repo = ".")

git_worktree_path(name, repo = ".")

git_worktree_add(name, path, branch, lock = FALSE, local = TRUE, repo = ".")

git_worktree_remove(name, repo = ".")

git_worktree_prune(
  name,
  prune_valid = FALSE,
```

```
  prune_locked = FALSE,
  prune_working_tree = FALSE,
  repo = "."
)

git_worktree_is_prunable(
  name,
  prune_valid = FALSE,
  prune_locked = FALSE,
  repo = "."
)

git_worktree_lock(name, repo = ".")

git_worktree_unlock(name, repo = ".")

git_worktree_is_locked(name, repo = ".")

git_worktree_is_valid(name, repo = ".")
```

## Arguments

| | |
|---|---|
| repo | The path to the git repository. If the directory is not a repository, parent directories are considered (see git_find). To disable this search, provide the filepath protected with I(). When using this parameter, always explicitly call by name (i.e. repo = ) because future versions of gert may have additional parameters. |
| name | The name of the worktree. |
| path | The path to checkout branch into. Importantly, the path up to the folder name must exist, but the folder name itself must not exist yet and will be created. |
| branch | The branch to checkout into path. |
| lock | Whether or not to lock the worktree on creation. |
| local | set TRUE to only check for local branches, FALSE to check for remote branches. Use NULL to return all branches. |
| prune_valid | Whether or not to forcibly prune a *valid* worktree. |
| prune_locked | Whether or not to forcibly prune a *locked* worktree. |
| prune_working_tree | Whether or not to also remove the folder that the worktree was using, i.e. the path supplied to git_worktree_add(). |

## See Also

Other git: git_archive, git_branch(), git_commit(), git_config(), git_diff(), git_fetch(), git_ignore, git_merge(), git_rebase(), git_remote, git_repo, git_reset(), git_signature(), git_stash, git_tag

## Examples

```
repo <- git_init(tempfile("gert-examples-repo"))

writeLines("hello", file.path(repo, 'hello.txt'))
git_add('hello.txt', repo = repo)
git_commit("First commit", author = "jeroen <jeroen@blabla.nl>", repo = repo)

# Create a branch that is going to be used for the worktree,
# but don't check it out!
git_branch_create(branch = "branch", checkout = FALSE, repo = repo)

path <- tempfile("gert-examples-worktree")

# Add a worktree for this branch
git_worktree_add(
  name = "worktree",
  path = path,
  branch = "branch",
  repo = repo
)

# Worktree info
git_worktree_list(repo = repo)

# Note how the files are checked out here
dir(path, all.files = TRUE)

# And the branch that we are on at `path` is `"branch"`
git_branch(repo = path)

# Cleanup worktree, and the folder at `path`
git_worktree_remove("worktree", repo = repo)

# Cleanup repo
unlink(repo, recursive = TRUE)
```

---

# libgit2_config *Show libgit2 version and capabilities*

---

## Description

`libgit2_config()` reveals which version of libgit2 gert is using and which features are supported, such whether you are able to use ssh remotes.

## Usage

```
libgit2_config()
```

## Examples

```
libgit2_config()
```

---

`user_is_configured` *Test if a Git user is configured*

---

## Description

This function exists mostly to guard examples that rely on having a user configured, in order to make commits. `user_is_configured()` makes no distinction between local or global user config.

## Usage

```
user_is_configured(repo = ".")
```

## Arguments

| | |
|---|---|
| `repo` | An optional `repo`, in the sense of `git_open()`. |

## Value

`TRUE` if `user.name` and `user.email` are set locally or globally, `FALSE` otherwise.

## Examples

```
user_is_configured()
```

# Index


∗ **git**
git_archive, 2
git_branch, 3
git_commit, 5
git_config, 7
git_diff, 9
git_fetch, 9
git_ignore, 12
git_merge, 13
git_rebase, 15
git_remote, 16
git_repo, 17
git_reset, 18
git_signature, 19
git_stash, 20
git_tag, 22
git_worktree, 22

askpass, *10*

credentials::ssh_key_info, *10*

fast-forward, *11*

git_add *(*git_commit*)*, 5
git_ahead_behind *(*git_rebase*)*, 15
git_archive, 2, *4*, *6*, *8*, *9*, *11*, *12*, *14–17*, *19*, *21*, *22*, *24*
git_archive_zip *(*git_archive*)*, 2
git_branch, *3*, 3, *6*, *8*, *9*, *11*, *12*, *14–17*, *19*, *21*, *22*, *24*
git_branch_checkout *(*git_branch*)*, 3
git_branch_create *(*git_branch*)*, 3
git_branch_delete *(*git_branch*)*, 3
git_branch_exists *(*git_branch*)*, 3
git_branch_fast_forward *(*git_branch*)*, 3
git_branch_list, *4*
git_branch_list *(*git_branch*)*, 3
git_branch_move *(*git_branch*)*, 3
git_branch_set_upstream *(*git_branch*)*, 3
git_checkout_pull_request, 4
git_cherry_pick *(*git_rebase*)*, 15
git_clone *(*git_fetch*)*, 9
git_commit, *3*, *4*, 5, *8*, *9*, *11*, *12*, *14–17*, *19*, *21*, *22*, *24*
git_commit_all *(*git_commit*)*, 5
git_commit_descendant_of *(*git_commit*)*, 5
git_commit_id *(*git_commit*)*, 5
git_commit_info *(*git_commit*)*, 5
git_commit_stats *(*git_commit*)*, 5
git_config, *3*, *4*, *6*, 7, *9*, *11*, *12*, *14–17*, *19*, *21*, *22*, *24*
git_config_global *(*git_config*)*, 7
git_config_global_set *(*git_config*)*, 7
git_config_set *(*git_config*)*, 7
git_conflicts *(*git_commit*)*, 5
git_diff, *3*, *4*, *6*, *8*, 9, *11*, *12*, *14–17*, *19*, *21*, *22*, *24*
git_diff_patch *(*git_diff*)*, 9
git_fetch, *3*, *4*, *6*, *8*, *9*, 9, *11*, *12*, *14–17*, *19*, *21*, *22*, *24*
git_fetch(), *11*
git_fetch_pull_requests *(*git_checkout_pull_request*)*, 4
git_find, *2–4*, *6*, *7*, *9*, *11–19*, *21*, *22*, *24*
git_find *(*git_repo*)*, 17
git_ignore, *3*, *4*, *6*, *8*, *9*, *11*, 12, *14–17*, *19*, *21*, *22*, *24*
git_ignore_path_is_ignored *(*git_ignore*)*, 12
git_info *(*git_repo*)*, 17
git_init *(*git_repo*)*, 17
git_log *(*git_commit*)*, 5
git_ls *(*git_commit*)*, 5
git_merge, *3*, *4*, *6*, *8*, *9*, *11*, *12*, 13, *15–17*, *19*, *21*, *22*, *24*
git_merge_abort *(*git_merge*)*, 13
git_merge_analysis *(*git_merge*)*, 13
git_merge_find_base *(*git_merge*)*, 13

git_merge_stage_only (git_merge), 13
git_open, 14
git_open(), 26
git_pull, 15
git_pull (git_fetch), 9
git_pull(), 11
git_push, 22
git_push (git_fetch), 9
git_push(), 11
git_rebase, 3, 4, 6, 8, 9, 11, 12, 14, 15, 16, 17, 19, 21, 22, 24
git_rebase_commit (git_rebase), 15
git_rebase_list (git_rebase), 15
git_remote, 3, 4, 6, 8, 9, 11, 12, 14, 15, 16, 17, 19, 21, 22, 24
git_remote_add (git_remote), 16
git_remote_info (git_remote), 16
git_remote_list (git_remote), 16
git_remote_list(), 4, 10
git_remote_ls (git_fetch), 9
git_remote_refspecs (git_remote), 16
git_remote_remove (git_remote), 16
git_remote_set_pushurl (git_remote), 16
git_remote_set_url (git_remote), 16
git_repo, 3, 4, 6, 8, 9, 11, 12, 14–16, 17, 19, 21, 22, 24
git_reset, 3, 4, 6, 8, 9, 11, 12, 14–17, 18, 19, 21, 22, 24
git_reset_hard (git_reset), 18
git_reset_mixed (git_reset), 18
git_reset_soft (git_reset), 18
git_rm (git_commit), 5
git_signature, 3–6, 8, 9, 11, 12, 14–17, 19, 19, 21, 22, 24
git_signature_default (git_signature), 19
git_signature_default(), 5
git_signature_parse (git_signature), 19
git_stash, 3, 4, 6, 8, 9, 11, 12, 14–17, 19, 20, 22, 24
git_stash_drop (git_stash), 20
git_stash_list (git_stash), 20
git_stash_pop (git_stash), 20
git_stash_save (git_stash), 20
git_stat_files (git_commit), 5
git_status (git_commit), 5
git_submodule_add (git_submodule_list), 21
git_submodule_fetch (git_submodule_list), 21
git_submodule_info (git_submodule_list), 21
git_submodule_init (git_submodule_list), 21
git_submodule_list, 21
git_submodule_set_to (git_submodule_list), 21
git_tag, 3, 4, 6, 8, 9, 11, 12, 14–17, 19, 21, 22, 24
git_tag_create (git_tag), 22
git_tag_delete (git_tag), 22
git_tag_list (git_tag), 22
git_tag_push (git_tag), 22
git_worktree, 3, 4, 6, 8, 9, 11, 12, 14–17, 19, 21, 22, 22
git_worktree_add (git_worktree), 22
git_worktree_exists (git_worktree), 22
git_worktree_is_locked (git_worktree), 22
git_worktree_is_prunable (git_worktree), 22
git_worktree_is_valid (git_worktree), 22
git_worktree_list (git_worktree), 22
git_worktree_lock (git_worktree), 22
git_worktree_path (git_worktree), 22
git_worktree_prune (git_worktree), 22
git_worktree_remove (git_worktree), 22
git_worktree_unlock (git_worktree), 22

I(), 2–4, 6, 7, 9, 11–19, 21, 22, 24

libgit2_config, 25

user_is_configured, 26