

# Package ‘tfrmt’

January 24, 2026

**Title** Applies Display Metadata to Analysis Results Datasets

**Version** 0.3.0

**Description** Creates a framework to store and apply display metadata to Analysis Results Datasets (ARDs). The use of 'tfrmt' allows users to define table format and styling without the data, and later apply the format to the data.

**License** Apache License (>= 2)

**URL** <https://GSK-Biostatistics.github.io/tfrmt/>,  
<https://github.com/GSK-Biostatistics/tfrmt>

**BugReports** <https://github.com/GSK-Biostatistics/tfrmt/issues>

**Depends** R (>= 4.2.0)

**Imports** cli, dplyr, forcats, ggplot2, glue, gt (>= 1.1.0), jsonlite,  
magrittr, purrr, rlang, stringi, stringr (>= 1.6.0), tibble,  
tidyr, tidyselect

**Suggests** cards (>= 0.6.0), covr, ggfortify, knitr, patchwork,  
pharmaverseadam, rmarkdown, survival, testthat (>= 3.0.0),  
withr

**Config/testthat/edition** 3

**Encoding** UTF-8

**Language** en-GB

**LazyData** true

**RoxygenNote** 7.3.3

**NeedsCompilation** no

**Author** Becca Krouse [aut, cre],  
Christina Fillmore [aut] (ORCID:  
<<https://orcid.org/0000-0003-0595-2302>>),  
Ellis Hughes [aut] (ORCID: <<https://orcid.org/0000-0003-0637-4436>>),  
Karima Ahmad [aut] (ORCID: <<https://orcid.org/0000-0002-8784-1712>>),  
Shannon Haughton [aut],  
Dragoş Moldovan-Grünfeld [aut],

Alanah Jonas [aut],  
 GlaxoSmithKline Research & Development Limited [cph, fnd],  
 Atorus Research LLC [cph, fnd]

**Maintainer** Becca Krouse <becca.z.krouse@gsk.com>

**Repository** CRAN

**Date/Publication** 2026-01-24 06:10:02 UTC

## Contents

|                                  |    |
|----------------------------------|----|
| apply_frmt . . . . .             | 3  |
| big_n_structure . . . . .        | 4  |
| body_plan . . . . .              | 5  |
| col_plan . . . . .               | 6  |
| col_style_plan . . . . .         | 8  |
| col_style_structure . . . . .    | 9  |
| data_ae . . . . .                | 10 |
| data_demog . . . . .             | 11 |
| data_efficacy . . . . .          | 11 |
| data_labs . . . . .              | 12 |
| display_row_frmts . . . . .      | 13 |
| display_val_frmts . . . . .      | 14 |
| element_block . . . . .          | 15 |
| element_row_grp_loc . . . . .    | 16 |
| footnote_plan . . . . .          | 17 |
| footnote_structure . . . . .     | 18 |
| frmt . . . . .                   | 19 |
| frmt_structure . . . . .         | 21 |
| is_frmt . . . . .                | 22 |
| json_to_tfrmt . . . . .          | 23 |
| layer_tfrmt . . . . .            | 23 |
| make_mock_data . . . . .         | 24 |
| page_plan . . . . .              | 25 |
| page_structure . . . . .         | 26 |
| param_set . . . . .              | 27 |
| prep_big_n . . . . .             | 28 |
| prep_combine_vars . . . . .      | 29 |
| prep_hierarchical_fill . . . . . | 30 |
| prep_label . . . . .             | 31 |
| print_mock_gt . . . . .          | 32 |
| print_to_ggplot . . . . .        | 33 |
| print_to_gt . . . . .            | 34 |
| row_grp_plan . . . . .           | 35 |
| row_grp_structure . . . . .      | 36 |
| shuffle_card . . . . .           | 37 |
| tfrmt . . . . .                  | 38 |
| tfrmt_n_pct . . . . .            | 42 |
| tfrmt_sigdig . . . . .           | 43 |

|                   |   |
|-------------------|---|
| <i>apply_frmt</i> | 3 |
|-------------------|---|

|                        |    |
|------------------------|----|
| tfmt_to_json . . . . . | 45 |
| update_group . . . . . | 45 |

|              |           |
|--------------|-----------|
| <b>Index</b> | <b>47</b> |
|--------------|-----------|

---

|                   |                         |
|-------------------|-------------------------|
| <i>apply_frmt</i> | <i>Apply formatting</i> |
|-------------------|-------------------------|

---

**Description**

Apply formatting

**Usage**

```
apply_frmt(frmt_def, .data, value, mock = FALSE, ...)

## S3 method for class 'frmt'
apply_frmt(frmt_def, .data, value, mock = FALSE, ...)

## S3 method for class 'frmt_combine'
apply_frmt(
  frmt_def,
  .data,
  value,
  mock = FALSE,
  param,
  column,
  label,
  group,
  ...
)

## S3 method for class 'frmt_when'
apply_frmt(frmt_def, .data, value, mock = FALSE, ...)
```

**Arguments**

|                 |                                                              |
|-----------------|--------------------------------------------------------------|
| <i>frmt_def</i> | formatting to be applied                                     |
| <i>.data</i>    | data, but only what is getting changed                       |
| <i>value</i>    | value symbol should only be one                              |
| <i>mock</i>     | Logical value is this is for a mock or not. By default FALSE |
| <i>...</i>      | additional arguments for methods                             |
| <i>param</i>    | param column as a quosure                                    |
| <i>column</i>   | column columns as a list of quosures                         |
| <i>label</i>    | label column as a quosure                                    |
| <i>group</i>    | group column as a list of quosures                           |

Value

formatted dataset

Examples

```
library(tibble)
library(dplyr)
# Set up data
df <- tibble(x = c(20.12,34.54,12.34))

apply_frmt(
  frmt_def = frmt("XX.X"),
  .data=df,
  value=quo(x))
```

---

|                 |                        |
|-----------------|------------------------|
| big_n_structure | <i>Big N Structure</i> |
|-----------------|------------------------|

---

Description

Big N structure allows you to specify which values should become the subject totals ("big N" values) and how they should be formatted in the table's column labels. Values are specified by providing the value(s) of the param column for which the values are big N's. This will remove these from the body of the table and place them into columns matching the values in the column column(s). The default formatting is N = xx, on its own line, but that can be changed by providing a different frmt() to n\_frmt.

Usage

```
big_n_structure(param_val, n_frmt = frmt("\nN = xx"), by_page = FALSE)
```

Arguments

|           |                                                                                                                                                                                                  |
|-----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| param_val | row value(s) of the parameter column for which the values are big N's                                                                                                                            |
| n_frmt    | <a href="#">frmt()</a> to control the formatting of the big N's                                                                                                                                  |
| by_page   | Option to include different big N's for each group-defined set of pages (defined by any variables set to ".default" in the page_plan). Default is FALSE, meaning only the overall Ns are applied |

Value

big\_n\_structure object

See Also

[Link to related article](#)

---

`body_plan`*Table Body Plan*

---

## Description

Define the formatting of the body contents of the table through a series of `frmt_structures`. Structures get applied in order from bottom up, so the last added structure is the first applied.

## Usage

```
body_plan(...)
```

## Arguments

`...` list of `frmt_structures` defining the body formatting

## Value

`body_plan` object

## See Also

[frmt\\_structure\(\)](#) defines which rows the formats will be applied to, and [frmt\(\)](#), [frmt\\_combine\(\)](#), and [frmt\\_when\(\)](#) define the format semantics.

[Link to related article](#)

## Examples

```
tfrmt_spec<- tfrmt(  
  title = "Table Title",  
  body_plan = body_plan(  
    frmt_structure(  
      group_val = c("group1"),  
      label_val = ".default",  
      frmt("XXX")  
    )  
  )  
)
```

col\_plan

*Define the Column Plan & Span Structures***Description**

Using `<tidy-select>` expressions and a series `span_structures`, define the order of the columns. The selection follows "last selected" principals, meaning columns are moved to the *last* selection as opposed to preserving the first location.

**Usage**

```
col_plan(..., .drop = FALSE)
```

```
span_structure(...)
```

**Arguments**

|                    |                                                                                                                                                                                                                                                                                                                                                        |
|--------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>...</code>   | For a <code>col_plan</code> and <code>span_structure</code> , <code>&lt;tidy-select&gt;</code> arguments, unquoted expressions separated by commas, and <code>span_structures</code> . <code>span_structures</code> must have the arguments named to match the name the column in the input data has to identify the correct columns. See the examples |
| <code>.drop</code> | Boolean. Should un-listed columns be dropped from the data. Defaults to <code>FALSE</code> .                                                                                                                                                                                                                                                           |

**Details****Column Selection:**

When `col_plan` gets applied and is used to create the output table, the underlying logic sorts out which column specifically is being selected. If a column is selected twice, the *last* instance in which the column is selected will be the location it gets rendered.

Avoid beginning the `col_plan()` column selection with a deselection (i.e. `col_plan(-col1)`, `col_plan(-starts_with("value"))`). This will result in the table preserving all columns not "de-selected" in the statement, and the order of the columns not changed. It is preferred when creating the `col_plan()` to identify all the columns planned on preserving in the order they are wished to appear, or if `<tidy-select>` arguments - such as `everything`- are used, identify the de-selection after the positive-selection.

Alternatively, once the gt table is produced, use the `cols_hide` function to remove un-wanted columns.

**Value**

`col_plan` object

`span_structure` object

**Images**

Here are some example outputs:

**See Also**

[Link to related article](#)

**Examples**

```
library(dplyr)

## select col_1 as the first column, remove col_last, then create spanning
## structures that have multiple levels
##
## examples also assume the tfrmt has the column argument set to c(c1, c2, c3)
##
spanning_col_plan_ex <- col_plan(
  col_1,
  -col_last,
  span_structure(
    c1 = "Top Label Level 1",
    c2 = "Second Label Level 1.1",
    c3 = c(col_3, col_4)
  ),
  span_structure(
    c1 = "Top Label Level 1",
    c2 = "Second Label Level 1.2",
    c3 = starts_with("B")
  ),
  span_structure(
    c1 = "Top Label Level 1",
    c3 = col_5
  ),
  span_structure(
    c2 = "Top Label Level 2",
    c3 = c(col_6, col_7)
  )
)

## select my_col_1 as the first column, then
## rename col_2 to new_col_1 and put as the
## second column, then select the rest of the columns
renaming_col_plan_ex <- col_plan(
  my_col_1,
  new_col_1 = col_2,
  everything()
)

renaming_col_plan_ex2 <- col_plan(
  my_col_1,
  new_col_1 = col_2,
  span_structure(
    c1 = c(`My Favorite span name` = "Top Label Level 1"),
    c3 = c(`the results column` = col_5)
  )
)
```

```
## To one or more stub headers rename the corresponding group/label variables in the column plan.
## If multiple group variables exist, any of them can be renamed.
## Note: Multiple stub headers are only possible if the `row_grp_plan` label
## location is set to "column". Otherwise, if more than one group/label column is renamed,
## {tfrmt} will use the highest level group name available.

renaming_group <- col_plan(
  my_grp = group, # rename group
  label,
  starts_with("col")
)
```

---

|                |                          |
|----------------|--------------------------|
| col_style_plan | <i>Column Style Plan</i> |
|----------------|--------------------------|

---

### Description

Define how the columns of the table body should be aligned, whether left, right or on a specific character(s).

### Usage

```
col_style_plan(...)
```

### Arguments

... series of col\_style\_structure objects

### Value

col\_style\_plan object

### See Also

[col\\_style\\_structure\(\)](#) for more information on how to specify how to and which columns to align.

[Link to related article](#)

### Examples

```
plan <- col_style_plan(
  col_style_structure(col = "my_var", align = "left", width = 100),
  col_style_structure(col = vars(four), align = "right"),
  col_style_structure(col = vars(two, three), align = c(".", " ", " "))
)
```

---

|                     |                               |
|---------------------|-------------------------------|
| col_style_structure | <i>Column Style Structure</i> |
|---------------------|-------------------------------|

---

**Description**

Column Style Structure

**Usage**

```
col_style_structure(  
  col,  
  align = NULL,  
  type = c("char", "pos"),  
  width = NULL,  
  ...  
)
```

**Arguments**

|       |                                                                                                                                                                                                |
|-------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| col   | Column value to align on from column variable. May be a quoted or unquoted column name, a tidyselect semantic, or a span_structure.                                                            |
| align | Alignment to be applied to column. Defaults to left alignment. See details for acceptable values.                                                                                              |
| type  | Type of alignment: "char" or "pos", for character alignment (default), and positional alignment, respectively. Positional alignment allows for aligning over multiple positions in the column. |
| width | Width to apply to the column in number of characters. Acceptable values include a numeric value, or a character string of a number.                                                            |
| ...   | These dots are for future extensions and must be empty                                                                                                                                         |

**Details**

Supports alignment and width setting of data value columns (values found in the column column). Row group and label columns are left-aligned by default. Acceptable input values for align differ by type = "char" or "pos":

**Character alignment (type = "char")::**

- "left" for left alignment
- "right" for right alignment
- supply a vector of character(s) to align on. If more than one character is provided, alignment will be based on the first occurrence of any of the characters. For alignment based on white space, leading white spaces will be ignored.

**Positional alignment (type = "pos")::**

supply a vector of strings covering all formatted cell values, with numeric values represented as x's. These values can be created manually or obtained by utilizing the helper display\_val\_frmts().

Alignment positions will be represented by vertical bars. For example, with starting values: `c("12.3", "(5%)", "2.35 (10.23)")` we can align all of the first sets of decimals and parentheses by providing `align = c("xxl.x", "ll(x%)", "xl.xx l")`

### Value

`col_style_structure` object

### See Also

[col\\_style\\_plan\(\)](#) for more information on how to combine `col_style_structure()`'s together to form a plan.

[Link to related article](#)

### Examples

```
plan <- col_style_plan(
  col_style_structure(col = "my_var",
    align = c("xx| |(xx%)",
      "xx|.x |(xx.x - xx.x)"),
    type = "pos", width = 100),
  col_style_structure(col = vars(four), align = "right", width = 200),
  col_style_structure(col = vars(two, three), align = c(".", ", ", " ")),
  col_style_structure(col = c(two, three), width = 25),
  col_style_structure(col = two, width = 25),
  col_style_structure(col = span_structure(span = value, col = val2),
    width = 25)
)
```

---

data\_ae

*Adverse Events Analysis Results Data*

---

### Description

A dataset containing the results needed for an AE table. Using the CDISC pilot data.

### Usage

`data_ae`

### Format

A data frame with 2,794 rows and 8 variables:

**AEBODSYS** highest level row labels: System Organ Class

**AETERM** more specific row labels: Preferred Term

**col2** higher level column names (spanners)

**col1** lower level column names  
**param** parameter to explain each value  
**value** values to put in a table  
**ord1** controls ordering  
**ord2** more ordering controls

---

data\_demog

*Demography Analysis Results Data*

---

### Description

A dataset containing the results needed for a demography table. Using the CDISC pilot data.

### Usage

data\_demog

### Format

A data frame with 386 rows and 7 variables:

**rowlbl1** highest level row labels  
**rowlbl2** more specific row labels  
**param** parameter to explain each value  
**grp** grouping column used to distinguish continuous and categorical  
**ord1** controls ordering  
**ord2** more ordering controls  
**column** column names  
**value** values to put in a table

---

data\_efficacy

*Efficacy Analysis Results Data*

---

### Description

A dataset containing the results needed for an Efficacy table. Using the CDISC pilot data for ADAS-Cog(11).

### Usage

data\_efficacy

**Format**

A data frame with 70 rows and 7 variables:

- group** highest level row labels
- label** more specific row labels
- column** column names
- param** parameter to explain each value
- value** values to put in a table
- ord1** controls ordering
- ord2** more ordering controls

---

|           |                                   |
|-----------|-----------------------------------|
| data_labs | <i>Labs Analysis Results Data</i> |
|-----------|-----------------------------------|

---

**Description**

A dataset containing the results needed for an labs results table. Using the CDISC pilot data.

**Usage**

data\_labs

**Format**

A data frame with 4,950 rows and 7 variables:

- group1** highest level row labels: Lab value class
- group2** more specific row labels: Lab parameter
- rowlbl** most specific row labels: Study visit
- col1** higher level column names (spanners)
- col2** lower level column names
- param** parameter to explain each value
- value** values to put in a table
- ord1** controls ordering
- ord2** more ordering controls
- ord3** more ordering controls

---

|                   |                                               |
|-------------------|-----------------------------------------------|
| display_row_frmts | <i>Display formatting applied to each row</i> |
|-------------------|-----------------------------------------------|

---

## Description

Used when debugging formatting, it is an easy way to allow you to see which formats are applied to each row in your dataset.

## Usage

```
display_row_frmts(tfrmt, .data, convert_to_txt = TRUE)
```

## Arguments

|                |                                                              |
|----------------|--------------------------------------------------------------|
| tfrmt          | tfrmt object to apply to the data                            |
| .data          | Data to apply the tfrmt to                                   |
| convert_to_txt | Logical value converting formatting to text, by default TRUE |

## Value

formatted tibble

## Examples

```
library(dplyr)
library(tidyr)

tfrmt_spec <- tfrmt(
  label = label,
  column = column,
  param = param,
  value=value,
  body_plan = body_plan(
    frmt_structure(group_val = ".default", label_val = ".default",
      frmt_combine(
        "{count} {percent}",
        count = frmt("xxx"),
        percent = frmt_when("==100" ~ frmt(""),
                           "==0" ~ "",
                           "TRUE" ~ frmt("(xx.x%)"))))
  ))

# Create data
df <- tidyr::crossing(label = c("label 1", "label 2"),
  column = c("placebo", "trt1"),
  param = c("count", "percent")) |>
  dplyr::mutate(value=c(24,19,2400/48,1900/38,5,1,500/48,100/38))

display_row_frmts(tfrmt_spec,df)
```

---

|                   |                                 |
|-------------------|---------------------------------|
| display_val_frmts | <i>Display formatted values</i> |
|-------------------|---------------------------------|

---

### Description

A helper for creating positional-alignment specifications for the `col_style_plan`. Returns all unique formatted values to appear in the column(s) specified. Numeric values are represented by x's.

### Usage

```
display_val_frmts(tfrmt, .data, mock = FALSE, col = NULL)
```

### Arguments

|                    |                                                                                                                                     |
|--------------------|-------------------------------------------------------------------------------------------------------------------------------------|
| <code>tfrmt</code> | tfrmt object to apply to the data                                                                                                   |
| <code>.data</code> | Data to apply the tfrmt to                                                                                                          |
| <code>mock</code>  | Mock table? TRUE or FALSE (default)                                                                                                 |
| <code>col</code>   | Column value to align on from column variable. May be a quoted or unquoted column name, a tidyselect semantic, or a span_structure. |

### Value

text representing character vector of formatted values to be copied and modified in the `col_style_plan`

### Examples

```
tf_spec <- tfrmt(
  group = c(rowlbl1, grp),
  label = rowlbl2,
  column = column,
  param = param,
  value = value,
  sorting_cols = c(ord1, ord2),
  body_plan = body_plan(
    frmt_structure(group_val = ".default", label_val = ".default", frmt_combine("{n} ({pct} %)",
                                          n = frmt("xxx"),
                                          pct = frmt("xx.x"))),
    frmt_structure(group_val = ".default", label_val = "n", frmt("xxx")),
    frmt_structure(group_val = ".default", label_val = c("Mean", "Median", "Min", "Max"),
                  frmt("xxx.x")),
    frmt_structure(group_val = ".default", label_val = "SD", frmt("xxx.xx")),
    frmt_structure(group_val = ".default", label_val = ".default",
                  p = frmt_when(">0.99" ~ ">0.99",
                                "<0.15" ~ "<0.15",
                                TRUE ~ frmt("x.xxx", missing = "")))
  ))

display_val_frmts(tf_spec, data_demog, col = vars(everything()))
display_val_frmts(tf_spec, data_demog, col = "p-value")
```

---

|               |                      |
|---------------|----------------------|
| element_block | <i>Element block</i> |
|---------------|----------------------|

---

**Description**

Element block

**Usage**

```
element_block(post_space = c(NULL, " ", "-"), fill = TRUE)
```

**Arguments**

|            |                                                                                         |
|------------|-----------------------------------------------------------------------------------------|
| post_space | Values to show in a new line created after the group block                              |
| fill       | Whether to recycle the value of post_space to match width of the data. Defaults to TRUE |

**Value**

element block object

**See Also**

[row\\_grp\\_plan\(\)](#) for more details on how to group row group structures, [row\\_grp\\_structure\(\)](#) for more details on how to specify row group structures, [element\\_row\\_grp\\_loc\(\)](#) for more details on how to specify whether row group titles span the entire table or collapse.

**Examples**

```
tfrmt_spec <- tfrmt(
  group = grp1,
  label = label,
  param = param,
  value = value,
  column = column,
  row_grp_plan = row_grp_plan(
    row_grp_structure(group_val = ".default", element_block(post_space = " "))
  ),
  body_plan = body_plan(
    frmt_structure(group_val = ".default", label_val = ".default", frmt("xx"))
  )
)
```

---

|                     |                                   |
|---------------------|-----------------------------------|
| element_row_grp_loc | <i>Element Row Group Location</i> |
|---------------------|-----------------------------------|

---

## Description

Element Row Group Location

## Usage

```
element_row_grp_loc(
  location = c("indented", "spanning", "column", "noprint", "gtdefault"),
  indent = " "
)
```

## Arguments

|          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| location | Location of the row group labels. Specifying 'indented' combines all group and label variables into a single column with each sub-group indented under its parent. 'spanning' and 'column' retain the highest level group variable in its own column and combine all remaining group and label variables into a single column with sub-groups indented. The highest level group column will either be printed as a spanning header or in its own column in the gt. The 'noprint' option allows the user to suppress group values from being printed. Finally, the 'gtdefault' option allows users to use the 'gt' defaults for styling multiple group columns. |
| indent   | A string of the number of spaces you want to indent                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |

## Value

element\_row\_grp\_loc object

## Images

Here are some example outputs:

## See Also

[row\\_grp\\_plan\(\)](#) for more details on how to group row group structures, [row\\_grp\\_structure\(\)](#) for more details on how to specify row group structures, [element\\_block\(\)](#) for more details on how to specify spacing between each group.

[Link to related article](#)

## Examples

```
tfrmt_spec <- tfrmt(
  group = c(grp1, grp2),
  label = label,
  param = param,
  value = value,
  column = column,
  row_grp_plan = row_grp_plan(label_loc = element_row_grp_loc(location = "noprint")),
  body_plan = body_plan(
    frmt_structure(group_val = ".default", label_val = ".default", frmt("xx"))
  )
)
```

---

footnote\_plan

*Footnote Plan*


---

## Description

Defining the location and content of footnotes with a series of footnote structures. Each structure is a footnote and can be applied in multiple locations.

## Usage

```
footnote_plan(..., marks = c("numbers", "letters", "standard", "extended"))
```

## Arguments

|                    |                                                                                                                                                                                                                                                                                         |
|--------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>...</code>   | a series of <code>footnote_structure()</code> separated by commas                                                                                                                                                                                                                       |
| <code>marks</code> | type of marks required for footnotes, properties inherited from <code>tab_footnote</code> in 'gt'. Available options are "numbers", "letters", "standard" and "extended" (standard for a traditional set of 4 symbols, extended for 6 symbols). The default option is set to "numbers". |

## Value

footnote plan object

## Examples

```
# Adds a footnote indicated by letters rather than numbers to Group 1
footnote_plan <- footnote_plan(
  footnote_structure(footnote_text = "Source Note", group_val = "Group 1"),
  marks="letters")

# Adds a footnote to the 'Placebo' column
footnote_plan <- footnote_plan(
  footnote_structure(footnote_text = "footnote", column_val = "Placebo"),
  marks="numbers")
```

---

|                    |                           |
|--------------------|---------------------------|
| footnote_structure | <i>Footnote Structure</i> |
|--------------------|---------------------------|

---

## Description

Footnote Structure

## Usage

```
footnote_structure(
  footnote_text,
  column_val = NULL,
  group_val = NULL,
  label_val = NULL
)
```

## Arguments

|               |                                                                                               |
|---------------|-----------------------------------------------------------------------------------------------|
| footnote_text | string with text for footnote                                                                 |
| column_val    | string or a named list of strings which represent the column to apply the footnote to         |
| group_val     | string or a named list of strings which represent the value of group to apply the footnote to |
| label_val     | string which represents the value of label to apply the footnote to                           |

## Value

footnote structure object

## Examples

```
# Adds a source note aka a footnote without a symbol in the table
footnote_structure <- footnote_structure(footnote_text = "Source Note")

# Adds a footnote to the 'Placebo' column
footnote_structure <- footnote_structure(footnote_text = "Text",
                                         column_val = "Placebo")

# Adds a footnote to either 'Placebo' or 'Treatment groups' depending on which
# which is last to appear in the column vector
footnote_structure <- footnote_structure(footnote_text = "Text",
                                         column_val = list(col1 = "Placebo", col2= "Treatment groups"))

# Adds a footnote to the 'Adverse Event' label
footnote_structure <- footnote_structure("Text", label_val = "Adverse Event")
```

---

|      |                               |
|------|-------------------------------|
| frmt | <i>Table Value Formatting</i> |
|------|-------------------------------|

---

**Description**

These functions provide an abstracted way to approach to define formatting of table contents. By defining in this way, the formats can be layered to be more specific and general cell styling can be done first.

`frmt()` is the base definition of a format. This defines spacing, rounding, and missing behaviour.

`frmt_combine()` is used when two or more rows need to be combined into a single cell in the table. Each of the rows needs to have a defined `frmt()` and need to share a label.

`frmt_when()` is used when a rows format behaviour is dependent on the value itself and is written similarly to `dplyr::case_when()`. The left hand side of the equation is a "TRUE" for the default case or the right hand side of a boolean expression `">50"`.

**Usage**

```
frmt(expression, missing = NULL, scientific = NULL, transform = NULL, ...)
```

```
frmt_combine(expression, ..., missing = NULL)
```

```
frmt_when(..., missing = NULL)
```

**Arguments**

|            |                                                                                                                                                                                            |
|------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| expression | this is the string representing the intended format. See details: expression for more a detailed description.                                                                              |
| missing    | when a value is missing that is intended to be formatted, what value to place. See details: missing for more a detailed description.                                                       |
| scientific | a string representing the intended scientific notation to be appended to the expression. Ex. "e^XX" or "x10^XX".                                                                           |
| transform  | this is what should happen to the value prior to formatting, It should be a formula or function. Ex. <code>~.*100</code> if you want to convert a percent from a decimal prior to rounding |
| ...        | See details: ... for a detailed description.                                                                                                                                               |

**Details****expression:**

- `frmt()` All numbers are represented by "x". Any additional character are printed as-is. If additional X's present to the left of the decimal point than the value, they will be represented as spaces.
- `frmt_combine()` defines how the parameters will be combined as a `glue::glue()` statement. Parameters need to be equal to the values in the param column and defined in the expression as `"{param1} {param2}"`.

**missing:**

- `frmt()` Value to enter when the value is missing. When NULL, the value is "".
- `frmt_combine()` defines how when all values to be combined are missing. When NULL the value is "".

**...:**

- `frmt()` These dots are for future extensions and must be empty.
- `frmt_combine()` accepts named arguments defining the `frmt()` to be applied to which parameters before being combined.
- `frmt_when()` accepts a series of equations separated by commas, similar to `dplyr::case_when()`. The left hand side of the equation is a "TRUE" for the default case or the right hand side of a boolean expression "`>50`". The right hand side of the equation is the `frmt()` to apply when the left side evaluates to TRUE.

**Value**

frmt object

**See Also**

`body_plan()` combines the `frmt_structures` to be applied to the table body, and `frmt_structure()` defines which rows the formats will be applied to.

[Link to related article](#)

**Examples**

```
frmt("XXX %")

frmt("XX.XXX")

frmt("xx.xx", scientific = "x10^xx")

frmt_combine(
  "{param1} {param2}",
  param1 = frmt("XXX %"),
  param2 = frmt("XX.XXX")
)

frmt_when(
  ">3" ~ frmt("(X.X%)"),
  "<=3" ~ frmt("Undetectable")
)

frmt_when(
  "==100" ~ frmt(""),
  "==0" ~ "",
  "TRUE" ~ frmt("(XXX.X%)")
)
```

---

|                |                                |
|----------------|--------------------------------|
| frmt_structure | <i>Format Structure Object</i> |
|----------------|--------------------------------|

---

### Description

Function needed to create a frmt\_structure object, which is a building block of `body_plan()`. This specifies the rows the format will be applied to.

### Usage

```
frmt_structure(group_val = ".default", label_val = ".default", ...)
```

### Arguments

|           |                                                                                                                                                          |
|-----------|----------------------------------------------------------------------------------------------------------------------------------------------------------|
| group_val | A string or a named list of strings which represent the value of group should be when the given frmt is implemented                                      |
| label_val | A string which represent the value of label should be when the given frmt is implemented                                                                 |
| ...       | either a <code>frmt()</code> , <code>frmt_combine()</code> , or a <code>frmt_when()</code> object. This can be named to also specify the parameter value |

### Value

frmt\_structure object

### Images

Here are some example outputs:

### See Also

`body_plan()` combines the frmt\_structures to be applied to the table body, and `frmt()`, `frmt_combine()`, and `frmt_when()` define the format semantics.

[Link to related article](#)

### Examples

```
sample_structure <- frmt_structure(
  group_val = c("group1"),
  label_val = ".default",
  frmt("XXX")
)
## multiple group columns
sample_structure <- frmt_structure(
  group_val = list(grp_col1 = "group1", grp_col2 = "subgroup3"),
  label_val = ".default",
  frmt("XXX")
)
```

is\_frmt

*Check if input is a frmt***Description**

Check if input is a frmt

Check if input is a frmt\_combine

Check if input is a frmt\_when

Check if input is a frmt\_structure

Check if input is a row\_grp\_structure

**Usage**

is\_frmt(x)

is\_frmt\_combine(x)

is\_frmt\_when(x)

is\_frmt\_structure(x)

is\_row\_grp\_structure(x)

**Arguments**

x                      Object to check

**Value**

'TRUE' if yes, 'FALSE' if no

**Examples**

```

x1 <- frmt("XXX.XX")
is_frmt(x1)

x2 <- frmt_combine("XXX %", "XX,XXX")
is_frmt_combine(x2)

x2 <- frmt_when(
  ">3" ~ frmt("(X.X%)"),
  "<=3" ~ frmt("Undetectable")
)
is_frmt_when(x2)

x3 <- frmt_structure(
  group_val = c("group1"),

```

```

    label_val = ".default",
    frmt("XXX")
  )
  is_frmt_structure(x3)

x4 <- row_grp_structure(group_val = c("A","C"), element_block(post_space = "---"))
is_row_grp_structure(x4)

```

---

|               |                      |
|---------------|----------------------|
| json_to_tfrmt | <i>json to tfrmt</i> |
|---------------|----------------------|

---

### Description

Reader to read JSON files/objects into tfrmt objects

### Usage

```
json_to_tfrmt(path = NULL, json = NULL)
```

### Arguments

|      |                                                                                                                                                                                           |
|------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| path | location of the json file to read in                                                                                                                                                      |
| json | json object to read in. By default this is null. This function will read in json object preferentially. So if both a path and a json object are supplied the json object will be read in. |

---

|             |                                     |
|-------------|-------------------------------------|
| layer_tfrmt | <i>Layer tfrmt objects together</i> |
|-------------|-------------------------------------|

---

### Description

Provide utility for layering tfrmt objects together. If both tfrmt's have values, it will preferentially choose the second tfrmt by default. This is an alternative to piping together tfrmt's

### Usage

```
layer_tfrmt(x, y, ..., join_body_plans = TRUE)
```

### Arguments

|                 |                                                                                                              |
|-----------------|--------------------------------------------------------------------------------------------------------------|
| x, y            | tfrmt objects that need to be combined                                                                       |
| ...             | arguments passed to layer_tfrmt_arg functions for combining different tfrmt elements                         |
| join_body_plans | should the body_plans be combined, or just keep styling in y. See details: join_body_plans for more details. |

Details

**join\_body\_plan:**  
When combining two body\_plans, the body plans will stack together, first the body plan from x tfrmt then y tfrmt. This means that frmt\_structures in y will take priority over those in x.  
Combining two tfrmt with large body\_plans can lead to slow table evaluation. Consider setting join\_body\_plan to FALSE. Only the y body\_plan will be preserved.

Value

tfrmt object

Examples

```
tfrmt_1 <- tfrmt(title = "title1")  
  
tfrmt_2 <- tfrmt(title = "title2", subtitle = "subtitle2")  
  
layered_table_format <- layer_tfrmt(tfrmt_1, tfrmt_2)
```

---

|                |                                          |
|----------------|------------------------------------------|
| make_mock_data | <i>Make mock data for display shells</i> |
|----------------|------------------------------------------|

---

Description

Make mock data for display shells

Usage

```
make_mock_data(tfrmt, .default = 1:3, n_cols = NULL)
```

Arguments

|          |                                                                                                                                                                                            |
|----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| tfrmt    | tfrmt object                                                                                                                                                                               |
| .default | Number of unique levels to create for group/label values set to ".default"                                                                                                                 |
| n_cols   | Number of columns in the output table (not including group/label variables). If not supplied it will default to using the col_plan from the tfrmt. If neither are available it will use 3. |

Value

tibble containing mock data

Examples

```
tfrmt_spec <- tfrmt(
  label = label,
  column = column,
  param = param,
  value=value,
  body_plan = body_plan(
    frmt_structure(group_val=".default", label_val=".default", frmt("xx.x"))
  )
)

make_mock_data(tfrmt_spec)
```

---

|           |           |
|-----------|-----------|
| page_plan | Page Plan |
|-----------|-----------|

---

Description

Defining the location and/or frequency of page splits with a series of `page_structure`'s and the `row_every_n` argument, respectively.

Usage

```
page_plan(
  ...,
  note_loc = c("noprint", "preheader", "subtitle", "source_note"),
  max_rows = NULL,
  transform = NULL
)
```

Arguments

|           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|-----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ...       | a series of <a href="#">page_structure()</a> separated by commas                                                                                                                                                                                                                                                                                                                                                                                                         |
| note_loc  | Location of the note describing each table's subset value(s). Useful if the <code>page_structure</code> contains only ".default" values (meaning the table is split by every unique level of a grouping variable), and that variable is dropped in the <code>col_plan</code> . <code>preheader</code> only available for <code>rtf</code> output.                                                                                                                        |
| max_rows  | Option to set a maximum number of rows per page. Takes a numeric value.                                                                                                                                                                                                                                                                                                                                                                                                  |
| transform | <b>[Experimental]</b> optional, a function or formula to transform the page label. It should take a character vector as input and return a modified character vector as output.<br><b>A function</b> is used as is, e.g. <code>function(x) {stringr::str_replace(x, "grp", "Group")}</code><br><b>A formula</b> , e.g. <code>~ stringr::str_remove_all(.x, "_")</code> is converted to a function. This allows you to create more compact anonymous functions (lambdas). |

**Value**

page\_plan object

**Examples**

```
# use of page_struct
page_plan(
  page_structure(
    group_val = "grp1",
    label_val = "lbl1"
  )
)

# use of # rows
page_plan(
  max_rows = 5
)

# use of transform with a formula
page_plan(
  page_structure(group_val = ".default"),
  transform = ~ stringr::str_replace(.x, "grp", "Group")
)

# use of transform with a function
transformation_function <- function(x) {
  stringr::str_replace(x, "grp", "Group")
}

page_plan(
  page_structure(group_val = ".default"),
  transform = transformation_function
)
```

---

page\_structure

*Page structure*

---

**Description**

Page structure

**Usage**

```
page_structure(group_val = NULL, label_val = NULL)
```

**Arguments**

|           |                                                                                                                                                                            |
|-----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| group_val | string or a named list of strings which represent the value of group to split after. Set to ".default" if the split should occur after every unique value of the variable. |
| label_val | string which represents the value of label to split after. Set to ".default" if the split should occur after every unique value of the variable.                           |

**Value**

page structure object

**Examples**

```
# split page after every unique level of the grouping variable
page_structure(group_val = ".default", label_val = NULL)

# split page after specific levels
page_structure(group_val = "grp1", label_val = "lbl3")
```

---

param\_set

---

Set custom parameter-level significant digits rounding

---

**Description**

Set custom parameter-level significant digits rounding

**Usage**

```
param_set(...)
```

**Arguments**

... Series of name-value pairs, optionally formatted using glue::glue() syntax (note glue syntax is required for combined parameters). The name represents the parameter and the value represents the number of places to round the parameter to. For combined parameters (e.g., "{min}, {max}"), value should be a vector of the same length (e.g., c(1,1)).

**Details**

Type param\_set() in console to view package defaults. Use of the function will add to the defaults and/or override included defaults of the same name. For values that are integers, use NA so no decimal places will be added.

**Value**

list of default parameter-level significant digits rounding

**Examples**

```
# View included defaults
param_set()

# Update the defaults
param_set("{mean} ({sd})" = c(2,3), "pct" = 1)

# Separate mean and SD to different lines
param_set("mean" = 2, "sd" = 3)

# Add formatting using the glue syntax
param_set("{pct} %" = 1)
```

---

|            |                                    |
|------------|------------------------------------|
| prep_big_n | <i>Prepare bigN stat variables</i> |
|------------|------------------------------------|

---

**Description****[Experimental]**

prep\_big\_n():

- recodes the "n" stat\_name into bigN for the desired variables, and
- drops all other stat\_names for the same variables.

If your tfrmt contains a [big\\_n\\_structure\(\)](#) you pass the tfrmt column to prep\_big\_n() via vars.

**Usage**

```
prep_big_n(df, vars)
```

**Arguments**

|      |                                                        |
|------|--------------------------------------------------------|
| df   | (data.frame)                                           |
| vars | (character) a vector of variables to prepare bigN for. |

**Value**

a data.frame with the same columns as the input. The stat\_name column is modified.

## Examples

```
df <- data.frame(
  stat_name = c("n", "max", "min", rep(c("n", "N", "p"), times = 2)),
  context = rep(c("continuous", "hierarchical", "categorical"), each = 3),
  stat_variable = rep(c("a", "b", "c"), each = 3)
) |>
dplyr::bind_rows(
  data.frame(
    stat_name = "n",
    context = "total_n",
    stat_variable = "d"
  )
)

prep_big_n(
  df,
  vars = c("b", "c")
)
```

---

|                   |                          |
|-------------------|--------------------------|
| prep_combine_vars | <i>Combine variables</i> |
|-------------------|--------------------------|

---

## Description

### [Experimental]

A wrapper around `tidyr::unite()` which pastes several columns into one. In addition it checks the output is identical to `dplyr::coalesce()`. If not identical, the input `data.frame` is returned unchanged. Useful for uniting sparsely populated columns, for example when processing an `ard` that was created with `cards::ard_stack()` then shuffled with `[shuffle_card()]`.

If the data is the result of a hierarchical `ard` stack (with `cards::ard_stack_hierarchical()` or `cards::ard_stack_hierarchical_count()`), the input is returned unchanged. This is assessed from the information in the `context` column which needs to be present. If the input data does not have a `context` column, the input will be returned unmodified.

## Usage

```
prep_combine_vars(df, vars, remove = TRUE)
```

## Arguments

|                     |                                                                                                                               |
|---------------------|-------------------------------------------------------------------------------------------------------------------------------|
| <code>df</code>     | ( <code>data.frame</code> )                                                                                                   |
| <code>vars</code>   | ( <code>character</code> ) a vector of variables to unite. If a single variable is supplied, the input is returned unchanged. |
| <code>remove</code> | If <code>TRUE</code> , remove input columns from output data frame.                                                           |

## Value

a `data.frame` with an additional column, called `variable_level` or the input unchanged.

**Examples**

```
df <- data.frame(
  a = 1:6,
  context = rep("categorical", 6),
  b = c("a", rep(NA, 5)),
  c = c(NA, "b", rep(NA, 4)),
  d = c(NA, NA, "c", rep(NA, 3)),
  e = c(NA, NA, NA, "d", rep(NA, 2)),
  f = c(NA, NA, NA, NA, "e", NA),
  g = c(rep(NA, 5), "f")
)

prep_combine_vars(
  df,
  vars = c("b", "c", "d", "e", "f", "g")
)
```

---

```
prep_hierarchical_fill
```

*Fill missing values in hierarchical variables*

---

**Description****[Experimental]**

Replace NA values in one column conditional on the same row having a non-NA value in a different column.

The user supplies a vector of columns from which the pairs will be extracted with a rolling window. For example `vars <- c("A", "B", "C")` will generate 2 pairs ("A", "B") and ("B", "C"). Therefore the order of the variables matters.

In each pair the second column B will be filled if A is not missing. One can choose the value to fill with:

- "Any {colname}", in this case evaluating to "Any B" is the default.
- Any other value. For example "Any event" for an adverse effects table.
- the value of pair's first column. In this case, the value of A.

**Usage**

```
prep_hierarchical_fill(
  df,
  vars,
  fill = "Any {colname}",
  fill_from_left = FALSE
)
```

**Arguments**

|                |                                                                                                                                          |
|----------------|------------------------------------------------------------------------------------------------------------------------------------------|
| df             | (data.frame)                                                                                                                             |
| vars           | (character) a vector of variables to generate pairs from.                                                                                |
| fill           | (character) value to replace with. Defaults to "Any {colname}", in which case colname will be replaced with the name of the column.      |
| fill_from_left | (logical) indicating whether to fill from the left (first) column in the pair. Defaults to FALSE. If TRUE it takes precedence over fill. |

**Value**

a data.frame with the same columns as the input, but in which some the desired columns have been filled pairwise.

**Examples**

```
df <- data.frame(
  x = c(1, 2, NA),
  y = c("a", NA, "b"),
  z = rep(NA, 3)
)

prep_hierarchical_fill(
  df,
  vars = c("x", "y")
)

prep_hierarchical_fill(
  df,
  vars = c("x", "y"),
  fill = "foo"
)

prep_hierarchical_fill(
  df,
  vars = c("x", "y", "z"),
  fill_from_left = TRUE
)
```

---

```
prep_label
```

---



---

*Prepare label*

---

**Description****[Experimental]**

Adds a label column which is a combination of stat\_label (for continuous variables) and variable\_level (for categorical ones) if these 2 columns are present in the input data frame.

Usage

```
prep_label(df)
```

Arguments

```
df (data.frame)
```

Value

a data.frame with a label column (if the input has the required columns) or the input unchanged.

Examples

```
df <- data.frame(
  variable_level = c("d", "e", "f"),
  stat_label = c("a", "b", "c"),
  stat_name = c("n", "N", "n"),
  context = c("categorical", "continuous", "hierarchical")
)

prep_label(df)
```

---

|               |                               |
|---------------|-------------------------------|
| print_mock_gt | <i>Print mock table to GT</i> |
|---------------|-------------------------------|

---

Description

Print mock table to GT

Usage

```
print_mock_gt(
  tfrmt,
  .data = NULL,
  .default = 1:3,
  n_cols = NULL,
  .unicode_ws = TRUE
)
```

Arguments

|             |                                                                                                                                                                                           |
|-------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| tfrmt       | tfrmt the mock table will be based off of                                                                                                                                                 |
| .data       | Optional data. If this is missing, group values, labels values and parameter values will be estimated based on the tfrmt                                                                  |
| .default    | sequence to replace the default values if a dataset isn't provided                                                                                                                        |
| n_cols      | the number of columns. This will only be used if mock data isn't provided. If not supplied, it will default to using the col_plan from the tfrmt. If neither are available it will use 3. |
| .unicode_ws | Whether to convert white space to unicode in preparation for output                                                                                                                       |

**Value**

a stylized gt object

**Examples**

```
# Create tfrmt specification
tfrmt_spec <- tfrmt( label = label, column =
column, param = param, body_plan = body_plan( frmt_structure(group_val =
".default", label_val = ".default", frmt_combine( "{count} {percent}",
count = frmt("xxx"), percent = frmt_when("==100"~ frmt(""), "==0"~ "",
"TRUE" ~ frmt("(xx.x%)")))) ))

# Print mock table using default
print_mock_gt(tfrmt = tfrmt_spec)

# Create mock data
df <- tidyr::crossing(label = c("label 1", "label 2",
"label 3"), column = c("placebo", "trt1", "trt2"), param = c("count",
"percent"))

# Print mock table using mock data
print_mock_gt(tfrmt_spec, df)
```

---

print\_to\_ggplot

---

*Print to ggplot*


---

**Description**

Print to ggplot

**Usage**

```
print_to_ggplot(tfrmt, .data, ...)
```

**Arguments**

|       |                                                                   |
|-------|-------------------------------------------------------------------|
| tfrmt | tfrmt object that will dictate the structure of the ggplot object |
| .data | Data to style in order to make the ggplot object                  |
| ...   | Inputs to geom_text to modify the style of the table body         |

**Value**

a stylized ggplot object

Examples

```
# Create data
risk<-tibble(time=c(rep(c(0,1000,2000,3000),3)),
              label=c(rep("Obs",4),rep("Lev",4),rep("Lev+5FU",4)),
              value=c(630,372,256,11,620,360,266,8,608,425,328,14),
              param=rep("n",12))

table<-tfrmt(
  label = label ,
  column = time,
  param = param,
  value = value) |>
  print_to_ggplot(risk)

table
```

---

|             |                    |
|-------------|--------------------|
| print_to_gt | <i>Print to gt</i> |
|-------------|--------------------|

---

Description

Print to gt

Usage

```
print_to_gt(tfrmt, .data, .unicode_ws = TRUE)
```

Arguments

- tfrmt            tfrmt object that will dictate the structure of the table
- .data           Data to style in order to make the table
- .unicode\_ws    Whether to convert white space to unicode in preparation for output

Value

a stylized gt object

Examples

```
library(dplyr)
# Create tfrmt specification
tfrmt_spec <- tfrmt(
  label = label,
  column = column,
  param = param,
```

```

value=value,
body_plan = body_plan(
  frmt_structure(group_val = ".default", label_val = ".default",
    frmt_combine(
      "{count} {percent}",
      count = frmt("xxx"),
      percent = frmt_when("==100"~ frmt(""),
        "=="0"~ "",
        "TRUE" ~ frmt("(xx.x%)")))))
))

# Create data
df <- tidyr::crossing(label = c("label 1", "label 2"),
  column = c("placebo", "trt1"),
  param = c("count", "percent")) |>
  dplyr::mutate(value=c(24,19,2400/48,1900/38,5,1,500/48,100/38))

print_to_gt(tfrmt_spec,df)

```

---

row\_grp\_plan

*Row Group Plan*


---

## Description

Define the look of the table groups on the output. This function allows you to add spaces after blocks and allows you to control how the groups are viewed whether they span the entire table or are nested as a column.

## Usage

```
row_grp_plan(..., label_loc = element_row_grp_loc(location = "indented"))
```

## Arguments

... Row group structure objects separated by commas  
 label\_loc [element\\_row\\_grp\\_loc\(\)](#) object specifying location

## Value

row\_grp\_plan object

## See Also

[row\\_grp\\_structure\(\)](#) for more details on how to specify row group structures, [element\\_block\(\)](#) for more details on how to specify spacing between each group, [element\\_row\\_grp\\_loc\(\)](#) for more details on how to specify whether row group titles span the entire table or collapse.

[Link to related article](#)

## Examples

```
## single grouping variable example
sample_grp_plan <- row_grp_plan(
  row_grp_structure(group_val = c("A","C"), element_block(post_space = "---")),
  row_grp_structure(group_val = c("B"), element_block(post_space = " ")),
  label_loc = element_row_grp_loc(location = "column")
)

## example with multiple grouping variables
sample_grp_plan <- row_grp_plan(
  row_grp_structure(group_val = list(grp1 = "A", grp2 = "b"), element_block(post_space = " ")),
  label_loc = element_row_grp_loc(location = "spanning")
)
```

---

|                   |                                   |
|-------------------|-----------------------------------|
| row_grp_structure | <i>Row Group Structure Object</i> |
|-------------------|-----------------------------------|

---

## Description

Function needed to create a row\_grp\_structure object, which is a building block of [row\\_grp\\_plan\(\)](#)

## Usage

```
row_grp_structure(group_val = ".default", element_block)
```

## Arguments

|               |                                                                                                                     |
|---------------|---------------------------------------------------------------------------------------------------------------------|
| group_val     | A string or a named list of strings which represent the value of group should be when the given frmt is implemented |
| element_block | <code>element_block()</code> object to define the block styling                                                     |

## Value

row\_grp\_structure object

## See Also

[row\\_grp\\_plan\(\)](#) for more details on how to group row group structures, [element\\_block\(\)](#) for more details on how to specify spacing between each group.

[Link to related article](#)

## Examples

```
## single grouping variable example
row_grp_structure(group_val = c("A","C"), element_block(post_space = "---"))

## example with multiple grouping variables
row_grp_structure(group_val = list(grp1 = "A", grp2 = "b"), element_block(post_space = " "))
```

---

|              |                      |
|--------------|----------------------|
| shuffle_card | <i>Shuffle</i> cards |
|--------------|----------------------|

---

## Description

### [Experimental]

This function ingests an ARD object of class `card` and shuffles the information to prepare for analysis. Helpful for streamlining across multiple ARDs.

## Usage

```
shuffle_card(
  x,
  by = NULL,
  trim = TRUE,
  order_rows = TRUE,
  fill_overall = "Overall {colname}",
  fill_hierarchical_overall = "Any {colname}"
)
```

## Arguments

|                           |                                                                                                                                                                                                                                                                                                                                                                                                                        |
|---------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>x</code>            | an ARD data frame of class 'card'                                                                                                                                                                                                                                                                                                                                                                                      |
| <code>by</code>           | Grouping variable(s) used in calculations. Defaults to <code>NULL</code> . If available (i.e. if <code>x</code> comes from a stacking function), <code>attributes(x)\$by</code> will be used instead of <code>by</code> .                                                                                                                                                                                              |
| <code>trim</code>         | logical representing whether or not to trim away <code>fmt_fun</code> , <code>error</code> , and <code>warning</code> columns                                                                                                                                                                                                                                                                                          |
| <code>order_rows</code>   | logical representing whether or not to apply <code>cards::tidy_ard_row_order()</code> to sort the rows                                                                                                                                                                                                                                                                                                                 |
| <code>fill_overall</code> | scalar to fill missing grouping or variable levels. If a character is passed, then it is processed with <code>glue::glue()</code> where the <code>colname</code> element is available to inject into the string, e.g. <code>Overall {colname}</code> may resolve to <code>"Overall AGE"</code> for an <code>AGE</code> column. Default is <code>Overall {colname}</code> . If <code>NA</code> then no fill will occur. |

fill\_hierarchical\_overall

scalar to fill variable levels for overall hierarchical calculations. If a character is passed, then it is processed with `glue::glue()` where the `colname` element is available to inject into the string, e.g. Any `{colname}` may resolve to "Any AESOC" for an AESOC column. Default is Any `{colname}`. If NA then no fill will occur.

## Value

a tibble

## Examples

```
## Not run:
cards::bind_ard(
  cards::ard_categorical(cards::ADSL, by = "ARM", variables = "AGEGR1"),
  cards::ard_categorical(cards::ADSL, variables = "ARM")
) |>
  shuffle_card()

## End(Not run)
```

---

tfrmt

*Table Format*

---

## Description

tfrmt, or "table format" is a way to pre-define the non-data components of your tables, and how the data will be handled once added: i.e. title, footers, headers, span headers, and cell formats. In addition, tfrmt's can be layered, building from one table format to the next. For cases where only one value can be used, the newly defined tfrmt accepts the latest tfrmt

## Usage

```
tfrmt(
  tfrmt_obj,
  group = vars(),
  label = quo(),
  param = quo(),
  value = quo(),
  column = vars(),
  title,
  subtitle,
  row_grp_plan,
  body_plan,
  col_style_plan,
  col_plan,
  sorting_cols,
```

```

    big_n,
    footnote_plan,
    page_plan,
    ...
  )

```

## Arguments

|                |                                                                                                                       |
|----------------|-----------------------------------------------------------------------------------------------------------------------|
| tfrmt_obj      | a tfrmt object to base this new format off of                                                                         |
| group          | what are the grouping vars of the input dataset                                                                       |
| label          | what is the label column of the input dataset                                                                         |
| param          | what is the param column of the input dataset                                                                         |
| value          | what is the value column of the input dataset                                                                         |
| column         | what is the column names column in the input dataset                                                                  |
| title          | title of the table                                                                                                    |
| subtitle       | subtitle of the table                                                                                                 |
| row_grp_plan   | plan of the row groups blocking. Takes a <a href="#">row_grp_plan()</a>                                               |
| body_plan      | combination and formatting of the input data. Takes a <a href="#">body_plan()</a>                                     |
| col_style_plan | how to style columns including alignment (left, right, character) and width. Takes a <a href="#">col_style_plan()</a> |
| col_plan       | a col_plan object which is used to select, rename, and nest columns. Takes a <a href="#">col_plan()</a>               |
| sorting_cols   | which columns determine sorting of output                                                                             |
| big_n          | how to format subject totals ("big Ns") for inclusion in the column labels. Takes a <a href="#">big_n_structure()</a> |
| footnote_plan  | footnotes to be added to the table. Takes a <a href="#">footnote_plan()</a>                                           |
| page_plan      | pagination splits to be applied to the table. Takes a <a href="#">page_plan()</a>                                     |
| ...            | These dots are for future extensions and must be empty.                                                               |

## Details

### NSE and Argument Evaluation:

- tfrmt allows users to pass vars, quo, and unquoted expressions to a variety of arguments, such as group, label, param, value, column, and sorting\_cols. Users accustomed to tidyverse semantics should be familiar with this behaviour. However, there is an important behaviour difference between tfrmt and normal tidyverse functions. Because the data are not a part of tfrmt, it does not know when a value being passed to it is intended to be an unquoted expression representing a column name or an object from the environment. As such, it preferentially uses the value from the environment over preserving the entry as an expression. For example, if you have an object "my\_object" in your environment with the value "Hello world", and try to create a tfrmt as `tfrmt(column = my_object)`, it will take the value of "my\_object" over assuming the column argument is an unquoted expression and view the entry to column as "Hello World". To pass "my\_object" to tfrmt as a column name, use quotes around the value: `tfrmt(columnn = "my_object")`.

- Additionally, unquoted expressions that match `tfrmt`'s other argument names can cause unexpected results. It is recommended to put quotes around the value as such: `tfrmt(label = "group")`. In this case, the quoting will prevent `tfrmt` from assigning its group input value to the `label` value.

## Value

`tfrmt` object

## Images

Here are some example outputs:

## See Also

[Link to related article](#)

## Examples

```
tfrmt_spec <- tfrmt(
  label = label,
  column = column,
  param = param,
  value=value)

tfrmt_spec <- tfrmt(
  label = label,
  column = column,
  param = param,
  value=value,
# Set the formatting for values
  body_plan = body_plan(
    frmt_structure(
      group_val = ".default",
      label_val = ".default",
      frmt_combine("{n} {pct}",
        n = frmt("xxx"),
        pct = frmt_when(
          "==100" ~ "(100%)",
          "==0" ~ "",
          TRUE ~ frmt("(xx.x %)")
        )
      )
    ),
# Specify column styling plan
    col_style_plan = col_style_plan(
      col_style_structure(col = vars(everything()), align = c(".",",",", " "))
    )

tfrmt_spec <- tfrmt(
  group = group,
```

```

label = label,
column = column,
param = param,
value=value,
sorting_cols = c(ord1, ord2),
# specify value formatting
body_plan = body_plan(
  frmt_structure(
    group_val = ".default",
    label_val = ".default",
    frmt_combine("{n} {pct}",
      n = frmt("xxx"),
      pct = frmt_when(
        "==100" ~ "(100%)",
        "==0" ~ "",
        TRUE ~ frmt("(xx.x %)")
      )
    )
  ),
  frmt_structure(
    group_val = ".default",
    label_val = "n",
    frmt("xxx")
  ),
  frmt_structure(
    group_val = ".default",
    label_val = c("Mean", "Median", "Min", "Max"),
    frmt("xxx.x")
  ),
  frmt_structure(
    group_val = ".default",
    label_val = "SD",
    frmt("xxx.xx")
  ),
  frmt_structure(
    group_val = ".default",
    label_val = ".default",
    p = frmt("")
  ),
  frmt_structure(
    group_val = ".default",
    label_val = c("n", "<65 yrs", "<12 months", "<25"),
    p = frmt_when(
      ">0.99" ~ ">0.99",
      "<0.001" ~ "<0.001",
      TRUE ~ frmt("x.xxx", missing = "")
    )
  )
),
# remove extra cols
col_plan = col_plan(-grp,
  -starts_with("ord") ),
# Specify column styling plan

```

```

col_style_plan = col_style_plan(
  col_style_structure(col = vars(everything()), align = c(".", "", "", " "))
),

# Specify row group plan
row_grp_plan = row_grp_plan(
  row_grp_structure(
    group_val = ".default",
    element_block(post_space = " ")
  ),
  label_loc = element_row_grp_loc(location = "column")
)

)

```

tfrmt\_n\_pct

*N Percent Template*

### Description

This function creates an tfrmt for an n % table, so count based table. The parameter values for n and percent can be provided (by default it will assume n and pct). Additionally the frmt\_when for formatting the percent can be specified. By default 100% and 0% will not appear and everything between 99% and 100% and 0% and 1% will be rounded using greater than (>) and less than (<) signs respectively.

### Usage

```

tfrmt_n_pct(
  n = "n",
  pct = "pct",
  pct_frmt_when = frmt_when("==100" ~ frmt(""), ">99" ~ frmt(">99%"), "==" ~ "", "<1"
    ~ frmt("<1%"), "TRUE" ~ frmt("xx.x%")),
  tfrmt_obj = NULL
)

```

### Arguments

|               |                                                     |
|---------------|-----------------------------------------------------|
| n             | name of count (n) value in the parameter column     |
| pct           | name of percent (pct) value in the parameter column |
| pct_frmt_when | formatting to be used on the the percent values     |
| tfrmt_obj     | an optional tfrmt object to layer                   |

### Value

tfrmt object

**Examples**

```
print_mock_gt(tfrmt_n_pct())
```

---

tfrmt\_sigdig

---

*Create tfrmt object from significant digits spec*


---

**Description**

This function creates a tfrmt based on significant digits specifications for group/label values. The input data spec provided to sigdig\_df will contain group/label value specifications. tfrmt\_sigdig assumes that these columns are group columns unless otherwise specified. The user may optionally choose to pass the names of the group and/or label columns as arguments to the function.

**Usage**

```
tfrmt_sigdig(
  sigdig_df,
  group = vars(),
  label = quo(),
  param_defaults = param_set(),
  missing = NULL,
  tfrmt_obj = NULL,
  ...
)
```

**Arguments**

|                |                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| sigdig_df      | data frame containing significant digits formatting spec. Has 1 record per group/label value, and columns for relevant group and/or label variables, as well as a numeric column sigdig containing the significant digits rounding to be applied in addition to the default. If unique group/label values are represented in multiple rows, this will result in only one of the sigdig values being carried through in implementation. |
| group          | what are the grouping vars of the input dataset                                                                                                                                                                                                                                                                                                                                                                                        |
| label          | what is the label column of the input dataset                                                                                                                                                                                                                                                                                                                                                                                          |
| param_defaults | Option to override or add to default parameters.                                                                                                                                                                                                                                                                                                                                                                                       |
| missing        | missing option to be included in all frmts                                                                                                                                                                                                                                                                                                                                                                                             |
| tfrmt_obj      | an optional tfrmt object to layer                                                                                                                                                                                                                                                                                                                                                                                                      |
| ...            | These dots are for future extensions and must be empty.                                                                                                                                                                                                                                                                                                                                                                                |

## Details

### Formats covered:

Currently covers specifications for `frmt` and `frmt_combine`. `frmt_when` not supported and must be supplied in additional `tfrmt` that is layered on.

### Group/label variables:

If the group/label variables are not provided to the arguments, the `body_plan` will be constructed from the input data with the following behaviour:

- If no group or label are supplied, it will be assumed that all columns in the input data are group columns.
- If a label variable is provided, but nothing is specified for group, any leftover columns (i.e. not matching `sigdig` or the supplied label variable name) in the input data will be assumed to be group columns.
- If any group variable is provided, any leftover columns (i.e. not matching `sigdig` or the supplied group/label variable) will be disregarded.

## Value

`tfrmt` object with a `body_plan` constructed based on the significant digits data spec and param-level significant digits defaults.

## Examples

```
sig_input <- tibble::tribble(
  ~group1, ~group2, ~sigdig,
  "CHEMISTRY", ".default", 3,
  "CHEMISTRY", "ALBUMIN", 1,
  "CHEMISTRY", "CALCIUM", 1,
  ".default", ".default", 2
)

# Subset data for the example
data <- dplyr::filter(data_labs, group2 == "BASOPHILS", col1 %in% c("Placebo", "Xanomeline Low Dose"))
tfrmt_sigdig(sigdig_df = sig_input,
             group = vars(group1, group2),
             label = rowlbl,
             param_defaults = param_set("[{n}]" = NA)) |>
tfrmt(column = vars(col1, col2),
      param = param,
      value = value,
      sorting_cols = vars(ord1, ord2, ord3),
      col_plan = col_plan(~starts_with("ord"))) |>
print_to_gt(.data = data)
```

---

|               |                      |
|---------------|----------------------|
| tfrmt_to_json | <i>Print to JSON</i> |
|---------------|----------------------|

---

**Description**

Print to JSON

**Usage**

tfrmt\_to\_json(tfrmt, path = NULL)

**Arguments**

|       |                                                                                    |
|-------|------------------------------------------------------------------------------------|
| tfrmt | tfrmt to print                                                                     |
| path  | file path to save JSON to. If not provided the JSON will just print to the console |

**Value**

JSON

**Examples**

```
tfrmt(  
  label = label,  
  column = column,  
  param = param,  
  value=value) |>  
  tfrmt_to_json()
```

---

|              |                                      |
|--------------|--------------------------------------|
| update_group | <i>Remap group values in a tfrmt</i> |
|--------------|--------------------------------------|

---

**Description**

Remap group values in a tfrmt

**Usage**

update\_group(tfrmt, ...)

**Arguments**

|       |                                                      |
|-------|------------------------------------------------------|
| tfrmt | a tfrmt                                              |
| ...   | Use new_name = old_name to rename selected variables |

**Value**

A tfrmt with the group variables updated in all places  
tfrmt object with updated groups#'

**Examples**

```
tfrmt_spec <- tfrmt(  
  group = c(group1, group2),  
  body_plan = body_plan(  
    frmt_structure(  
      group_val = list(group2 = "value"),  
      label_val = ".default",  
      frmt("XXX")  
    ),  
    frmt_structure(  
      group_val = list(group1 = "value", group2 = "value"),  
      label_val = ".default",  
      frmt("XXX")  
    )  
  )  
)  
  
tfrmt_spec %>%  
  update_group(New_Group = group1)
```

# Index

## \* datasets

- data\_ae, [10](#)
- data\_demog, [11](#)
- data\_efficacy, [11](#)
- data\_labs, [12](#)

apply\_frmt, [3](#)

big\_n\_structure, [4](#)

big\_n\_structure(), [28](#), [39](#)

body\_plan, [5](#)

body\_plan(), [20](#), [21](#), [39](#)

cards::ard\_stack(), [29](#)

cards::ard\_stack\_hierarchical(), [29](#)

cards::ard\_stack\_hierarchical\_count(), [29](#)

col\_plan, [6](#)

col\_plan(), [39](#)

col\_style\_plan, [8](#)

col\_style\_plan(), [10](#), [39](#)

col\_style\_structure, [9](#)

col\_style\_structure(), [8](#)

cols\_hide, [6](#)

data\_ae, [10](#)

data\_demog, [11](#)

data\_efficacy, [11](#)

data\_labs, [12](#)

display\_row\_frmts, [13](#)

display\_val\_frmts, [14](#)

dplyr::case\_when(), [19](#), [20](#)

element\_block, [15](#)

element\_block(), [16](#), [35](#), [36](#)

element\_row\_grp\_loc, [16](#)

element\_row\_grp\_loc(), [15](#), [35](#)

everything, [6](#)

footnote\_plan, [17](#)

footnote\_plan(), [39](#)

footnote\_structure, [18](#)

footnote\_structure(), [17](#)

frmt, [19](#)

frmt(), [4](#), [5](#), [21](#)

frmt\_combine(frmt), [19](#)

frmt\_combine(), [5](#), [21](#)

frmt\_structure, [21](#)

frmt\_structure(), [5](#), [20](#)

frmt\_when(frmt), [19](#)

frmt\_when(), [5](#), [21](#)

glue::glue(), [37](#), [38](#)

is\_frmt, [22](#)

is\_frmt\_combine(is\_frmt), [22](#)

is\_frmt\_structure(is\_frmt), [22](#)

is\_frmt\_when(is\_frmt), [22](#)

is\_row\_grp\_structure(is\_frmt), [22](#)

json\_to\_tfrmt, [23](#)

layer\_tfrmt, [23](#)

make\_mock\_data, [24](#)

page\_plan, [25](#)

page\_plan(), [39](#)

page\_structure, [26](#)

page\_structure(), [25](#)

param\_set, [27](#)

prep\_big\_n, [28](#)

prep\_combine\_vars, [29](#)

prep\_hierarchical\_fill, [30](#)

prep\_label, [31](#)

print\_mock\_gt, [32](#)

print\_to\_ggplot, [33](#)

print\_to\_gt, [34](#)

row\_grp\_plan, [35](#)

row\_grp\_plan(), [15](#), [16](#), [36](#), [39](#)

row\_grp\_structure, [36](#)

`row_grp_structure()`, [15](#), [16](#), [35](#)

`shuffle_card`, [37](#)

`span_structure(col_plan)`, [6](#)

`tfrmt`, [38](#)

`tfrmt_n_pct`, [42](#)

`tfrmt_sigdig`, [43](#)

`tfrmt_to_json`, [45](#)

`update_group`, [45](#)