

# Program Flow in readJDX

Bryan A. Hanson<sup>a</sup>

<sup>a</sup>Dept. of Chemistry & Biochemistry, DePauw University; [hanson@depauw.edu](mailto:hanson@depauw.edu)

This version was compiled on August 7, 2021

This vignette is based on readJDX version 0.5.61.

## Program Flow

readJDX is coded in such a way that it should be easy to add features. Contributions to improve or expand the package, including pull requests, are always welcome! Table 1 shows the overall flow of the function calls. Only a couple of these functions are exported, so take a look at the source code for documentation. Be sure to check out the *MiniDIFDUP\_1* and *MiniDIFDUP\_2* vignettes for additional information about the JCAMP-DX file structure and how readJDX functions extract the data.

**Table 1. Program Flow.**

function	input
readJDX	file name
- findVariableLists	character vector: all lines from original file
- extractParams	character vector: just the metadata lines
- processVariableList	character vector: a single VL
-- processXYZ	character vector: a single VL
--- decompLines	character vector: a single VL
---- getComp	character vector: a single VL
---- unSQZ	character vector: named with the ASDF mode, called via lapply
---- insertDUPs	character vector: named with the ASDF mode, called via lapply
----- repDUPs	a string of length one
---- deDIF	*list* of character vectors from a single VL; the character vectors are named with the ASDF mode, the list is named with line numbers
----- unDIF	character vector: one line from VL, entries named by ASDF code
---- yValueCheck	*list* of character vectors from a single VL; the character vectors are named with the ASDF mode, the list is named with line numbers
-- processPT	character vector: a single VL
-- processDT	character vector: a single VL

*Note:*

VL stands for variable list, as defined in the JCAMP-DX standard. For examples see the *\*MiniDIFDUP\_1\** vignette.