

mkin -
Routines for fitting kinetic models with one or more
state variables to chemical degradation data

Johannes Ranke
Product Safety
Harlan Laboratories Ltd.
Zelgliweg 1, CH-4452 Itingen, Switzerland

May 5, 2011

Abstract

In the regulatory evaluation of chemical substances like plant protection products (pesticides), biocides and other chemicals, degradation data play an important role. For the evaluation of pesticide degradation experiments, detailed guidance has been developed, based on nonlinear optimisation. The R add-on package **mkin** implements fitting some of the models recommended in this guidance from within R and calculates some statistical measures for data series within one or more compartments, for parent and metabolites.

Contents

1	Introduction	1
2	Example	1
2.1	Data format	1
2.2	Model definition	2
2.3	Fitting the model	3

Key words: Kinetics, FOCUS, nonlinear optimisation

1 Introduction

Many approaches are possible regarding the evaluation of chemical degradation data. The **kinfit** package ([Ranke, 2010a](#)) in R ([R Development Core Team, 2010](#)) implements the approach recommended in the kinetics report provided by the FORum for Co-ordination of pesticide fate models and their USe ([FOCUS Work Group on Degradation Kinetics, 2006](#)) for simple data series for one parent compound in one compartment.

The **mkim** package ([Ranke, 2010b](#)) extends this approach to data series with metabolites and more than one compartment and includes the possibility for back reactions.

2 Example

In the following, requirements for data formatting are explained. Then the procedure for fitting the four kinetic models recommended by the FOCUS group to an example dataset for parent only given in the FOCUS kinetics report is illustrated. The explanations are kept rather verbose in order to lower the barrier for R newcomers.

2.1 Data format

The following listing shows example dataset C from the FOCUS kinetics report as distributed with the **mkim** package

```
R> library("mkim")
```

This product includes software developed by the University of Chicago, as Operator of Argonne National Laboratory.

See the LICENSE file distributed with the minpack.lm source code or <http://www.netlib.org/minpack/disclaimer> for the full license.

```
R> FOCUS_2006_C
```

	name	time	value
1	parent	0	85.1
2	parent	1	57.9
3	parent	3	29.9
4	parent	7	14.6
5	parent	14	9.7
6	parent	28	6.6
7	parent	63	4.0
8	parent	91	3.9
9	parent	119	0.6

Note that the data needs to be in the format of a data frame containing a variable **name** specifying the observed variable, indicating the compound name and, if applicable, the compartment, a variable **time** containing sampling times, and a numeric variable **value** specifying the observed value of the variable. If a further variable **error** is present, this will be used to give different weights to the data points (the higher the error, the lower the weight, see the help page of the **modCost** function of the **FME** package ([Soetaert and Petzoldt, 2010](#))). Replicate measurements are not recorded in extra columns but simply appended, leading to multiple occurrences of the sampling times **time**.

Small to medium size dataset can be conveniently entered directly as R code as shown in the following listing

```
R> example_data <- data.frame(  
+   name = rep("parent", 9),  
+   time = c(0, 1, 3, 7, 14, 28, 63, 91, 119),  
+   value = c(85.1, 57.9, 29.9, 14.6, 9.7, 6.6, 4, 3.9, 0.6)  
+ )
```

2.2 Model definition

The next task is to define the model to be fitted to the data. In order to facilitate this task, a convenience function **mkmod** is available.

```
R> SFO <- mkmod(parent = list(type = "SFO"))  
R> SFORB <- mkmod(parent = list(type = "SFORB"))  
R> SFO_SFO <- mkmod(  
+   parent = list(type = "SFO", to = "m1", sink = TRUE),  
+   m1 = list(type = "SFO"))  
R> SFORB_SFO <- mkmod(  
+   parent = list(type = "SFORB", to = "m1", sink = TRUE),  
+   m1 = list(type = "SFO"))
```

The model definitions given above define sets of linear first-order ordinary differential equations. In these cases, a coefficient matrix is also returned.

Other models that include time on the right-hand side of the differential equation are the first-order multi-compartment (FOMC) model and the Hockey-Stick (HS) model. At present, only the FOMC model can only be used, and only for the parent compound.

2.3 Fitting the model

Then the model parameters should be fitted to the data. The function `mkinfitt` internally creates a cost function using `modCost` from the **FME** package and the produces a fit using `modFit` from the same package. In cases of linear first-order differential equations, the solution used for calculating the cost function is based on the fundamental system of the coefficient matrix, as proposed by [Bates and Watts \(1988\)](#).

```
R> # Do not show significance stars as they interfere with vignette generation
R> options(show.signif.stars = FALSE)
R> SF0.fit <- mkinfit(SF0, FOCUS_2006_C)
```

```
Model cost at call 1 : 4718.953
Model cost at call 4 : 4718.953
Model cost at call 5 : 572.4065
Model cost at call 7 : 572.4065
Model cost at call 8 : 236.2068
Model cost at call 9 : 236.2068
Model cost at call 11 : 198.9361
Model cost at call 12 : 198.9361
Model cost at call 14 : 196.6776
Model cost at call 15 : 196.6776
Model cost at call 16 : 196.6776
Model cost at call 17 : 196.542
Model cost at call 18 : 196.542
Model cost at call 19 : 196.542
Model cost at call 20 : 196.5339
Model cost at call 21 : 196.5339
Model cost at call 22 : 196.5339
Model cost at call 23 : 196.5334
Model cost at call 25 : 196.5334
Model cost at call 26 : 196.5334
Model cost at call 28 : 196.5334
Model cost at call 29 : 196.5334
Model cost at call 33 : 196.5334
```

```
R> summary(SF0.fit)
```

Equations:

```
[1] d_parent = - k_parent_sink * parent
```

Starting values for optimised parameters:

	initial	type	lower	upper
parent_0	100.0	state	0	Inf
k_parent_sink	0.1	deparm	0	Inf

Fixed parameter values:

None

Optimised parameters:

	Estimate	Std. Error	t value	Pr(>t)
parent_0	82.4920	4.7402	17.402	2.54e-07
k_parent_sink	0.3061	0.0459	6.668	0.000143

Residual standard error: 5.299 on 7 degrees of freedom

Chi2 error levels in percent:

	err.min	n.optim	df
All data	15.84	2	7
parent	15.84	2	7

Estimated disappearance times:

	DT50	DT90
parent	2.265	7.523

Estimated formation fractions:

	ff
parent_sink	1

Data:

time	variable	observed	predicted	residual
0	parent	85.1	82.49198370359448518	2.608
1	parent	57.9	60.74234531346141353	-2.842
3	parent	29.9	32.93450758457527172	-3.035
7	parent	14.6	9.68211888229914663	4.918
14	parent	9.7	1.13639437242541330	8.564
28	parent	6.6	0.01565475954997405	6.584
63	parent	4.0	0.00000034869018191	4.000
91	parent	3.9	0.00000000006617202	3.900
119	parent	0.6	0.00000000000001256	0.600

R> SFORB.fit <- mkinfit(SFORB, FOCUS_2006_C)

Model cost at call	1 :	7044.136
Model cost at call	4 :	7044.136
Model cost at call	7 :	3460.19
Model cost at call	9 :	3460.19
Model cost at call	11 :	3460.19
Model cost at call	13 :	312.9896

```

Model cost at call 15 : 312.9896
Model cost at call 17 : 312.9896
Model cost at call 18 : 27.14661
Model cost at call 20 : 27.14661
Model cost at call 23 : 4.437653
Model cost at call 25 : 4.437653
Model cost at call 28 : 4.362927
Model cost at call 31 : 4.362927
Model cost at call 33 : 4.362715
Model cost at call 38 : 4.362714
Model cost at call 43 : 4.362714
Model cost at call 48 : 4.362714
Model cost at call 52 : 4.362714

```

```
R> summary(SFORB.fit)
```

Equations:

```

[1] d_parent_free = - k_parent_free_sink * parent_free - k_parent_free_bound * parent_free
[2] d_parent_bound = + k_parent_free_bound * parent_free - k_parent_bound_free * parent_free

```

Starting values for optimised parameters:

	initial	type	lower	upper
parent_free_0	100.0	state	0	Inf
k_parent_free_sink	0.1	deparm	0	Inf
k_parent_free_bound	0.1	deparm	0	Inf
k_parent_bound_free	0.1	deparm	0	Inf

Fixed parameter values:

	value	type
parent_bound	0	state

Optimised parameters:

	Estimate	Std. Error	t value	Pr(>t)
parent_free_0	85.002737	0.890671	95.437	1.20e-09
k_parent_free_sink	0.395044	0.014308	27.610	5.83e-07
k_parent_free_bound	0.061599	0.007289	8.451	0.00019
k_parent_bound_free	0.020764	0.003752	5.533	0.00132

Residual standard error: 0.9341 on 5 degrees of freedom

Chi2 error levels in percent:

	err.min	n.optim	df
All data	2.662	4	5
parent	2.662	4	5

Estimated disappearance times:

	DT50	DT90
parent	1.887	21.25

Estimated formation fractions:

```
          ff
parent_free_sink 1
```

Estimated Eigenvalues of SFORB model(s):

```
parent_b1 parent_b2
 0.45956   0.01785
```

Data:

time	variable	observed	predicted	residual
0	parent	85.1	85.003	0.09726
1	parent	57.9	58.039	-0.13912
3	parent	29.9	30.054	-0.15351
7	parent	14.6	13.866	0.73388
14	parent	9.7	9.787	-0.08657
28	parent	6.6	7.532	-0.93205
63	parent	4.0	4.033	-0.03269
91	parent	3.9	2.447	1.45348
119	parent	0.6	1.484	-0.88424

```
R> SFO_SFO.fit <- mkinfit(SFO_SFO, FOCUS_2006_D, plot=TRUE)
```

```
Model cost at call 1 : 18994.29
Model cost at call 3 : 18994.29
Model cost at call 7 : 10641.39
Model cost at call 8 : 10641.39
Model cost at call 12 : 7145.459
Model cost at call 14 : 7145.458
Model cost at call 17 : 411.9739
Model cost at call 18 : 411.9738
Model cost at call 22 : 371.2194
Model cost at call 23 : 371.2194
Model cost at call 27 : 371.2127
Model cost at call 28 : 371.2127
Model cost at call 29 : 371.2127
Model cost at call 31 : 371.2127
Model cost at call 32 : 371.2127
Model cost at call 34 : 371.2127
Model cost at call 37 : 371.2127
Model cost at call 39 : 371.2127
```

```
R> summary(SFO_SFO.fit, data=FALSE)
```

Equations:

```
[1] d_parent = - k_parent_sink * parent - k_parent_m1 * parent
[2] d_m1 = - k_m1_sink * m1 + k_parent_m1 * parent
```

Starting values for optimised parameters:

	initial	type	lower	upper
parent_0	100.0	state	0	Inf

<i>k_parent_sink</i>	0.1	deparm	0	Inf
<i>k_m1_sink</i>	0.1	deparm	0	Inf
<i>k_parent_m1</i>	0.1	deparm	0	Inf

Fixed parameter values:

	value	type
<i>m1</i>	0	state

Optimised parameters:

	Estimate	Std. Error	t value	Pr(>t)
<i>parent_0</i>	9.960e+01	1.614e+00	61.720	< 2e-16
<i>k_parent_sink</i>	4.792e-02	3.750e-03	12.778	3.05e-15
<i>k_m1_sink</i>	5.261e-03	7.159e-04	7.349	5.76e-09
<i>k_parent_m1</i>	5.078e-02	2.094e-03	24.248	< 2e-16

Residual standard error: 3.211 on 36 degrees of freedom

Chi2 error levels in percent:

	err.min	n.optim	df
All data	6.565	4	16
parent	6.827	3	6
m1	4.748	1	10

Estimated disappearance times:

	DT50	DT90
parent	7.023	23.33
m1	131.760	437.70

Estimated formation fractions:

	ff
<i>parent_sink</i>	0.4855
<i>parent_m1</i>	0.5145
<i>m1_sink</i>	1.0000

```
R> SFORB_SF0.fit <- mkinfit(SFORB_SF0, FOCUS_2006_D, plot=TRUE)
```

```
Model cost at call 1 : 16413.78
Model cost at call 3 : 16413.78
Model cost at call 10 : 3061.064
Model cost at call 11 : 3061.063
Model cost at call 17 : 392.3431
Model cost at call 18 : 392.3431
Model cost at call 20 : 392.3431
Model cost at call 22 : 392.3431
Model cost at call 25 : 354.9442
Model cost at call 27 : 354.9442
Model cost at call 31 : 354.9442
Model cost at call 33 : 354.6583
Model cost at call 35 : 354.6583
```



```

Model cost at call 39 : 354.6583
Model cost at call 40 : 352.5954
Model cost at call 42 : 352.5954
Model cost at call 46 : 352.5954
Model cost at call 48 : 352.2551
Model cost at call 50 : 352.2551
Model cost at call 54 : 352.2551
Model cost at call 56 : 352.2077
Model cost at call 58 : 352.2077
Model cost at call 62 : 352.2077
Model cost at call 65 : 352.2057
Model cost at call 66 : 352.2057
Model cost at call 68 : 352.2057
Model cost at call 72 : 352.2049
Model cost at call 74 : 352.2049
Model cost at call 80 : 352.2047
Model cost at call 83 : 352.2047
Model cost at call 88 : 352.2047
Model cost at call 90 : 352.2047
Model cost at call 95 : 352.2047
Model cost at call 100 : 352.2047

```

```
R> summary(SFORB_SFO.fit, data=FALSE)
```

Equations:

```

[1] d_parent_free = - k_parent_free_sink * parent_free - k_parent_free_bound * parent_free
[2] d_parent_bound = + k_parent_free_bound * parent_free - k_parent_bound_free * parent_free
[3] d_m1 = - k_m1_sink * m1 + k_parent_free_m1 * parent_free

```

Starting values for optimised parameters:

	initial	type	lower	upper
parent_free_0	100.0	state	0	Inf
k_parent_free_sink	0.1	deparm	0	Inf
k_parent_free_bound	0.1	deparm	0	Inf
k_parent_bound_free	0.1	deparm	0	Inf
k_m1_sink	0.1	deparm	0	Inf
k_parent_free_m1	0.1	deparm	0	Inf

Fixed parameter values:

	value	type
parent_bound	0	state
m1	0	state

Optimised parameters:

	Estimate	Std. Error	t value	Pr(>t)
parent_free_0	1.011e+02	2.020e+00	50.033	< 2e-16
k_parent_free_sink	6.407e-02	2.691e-02	2.381	0.01151
k_parent_free_bound	1.680e-01	5.144e-01	0.327	0.37298
k_parent_bound_free	5.239e-01	8.547e-01	0.613	0.27199

<i>k_{m1}</i> _sink	5.213e-03	7.210e-04	7.230	1.15e-08
<i>k_{parent}</i> _free_ <i>m1</i>	6.563e-02	2.543e-02	2.581	0.00717

Residual standard error: 3.219 on 34 degrees of freedom

Chi2 error levels in percent:

	err.min	n.optim	df
All data	6.645	6	14
parent	7.207	5	4
<i>m1</i>	5.123	1	10

Estimated disappearance times:

	DT50	DT90
parent	6.805	24.05
<i>m1</i>	132.971	441.72

Estimated formation fractions:

	ff
parent_free_sink	0.494
parent_free_ <i>m1</i>	0.506
<i>m1</i> _sink	1.000

Estimated Eigenvalues of SFORB model(s):

parent_b1	parent_b2
0.7283	0.0933

References

- D.~Bates and D.~Watts. *Nonlinear regression and its applications*. Wiley-Interscience, 1988.
- FOCUS Work Group on Degradation Kinetics. *Guidance Document on Estimating Persistence and Degradation Kinetics from Environmental Fate Studies on Pesticides in EU Registration. Report of the FOCUS Work Group on Degradation Kinetics*, 2006. URL <http://focus.jrc.ec.europa.eu/dk>. EC Document Reference Sanco/10058/2005 version 2.0.
- R Development Core Team. *R: A Language and Environment for Statistical Computing*. R Foundation for Statistical Computing, Vienna, Austria, 2010. URL <http://www.R-project.org>. ISBN 3-900051-07-0.
- Johannes Ranke. *kinfit: Routines for fitting simple kinetic models to chemical degradation data*, 2010a. URL <http://CRAN.R-project.org>.
- Johannes Ranke. *mkln: Routines for fitting kinetic models with one or more state variables to chemical degradation data*, 2010b. URL <http://CRAN.R-project.org>.

Karline Soetaert and Thomas Petzoldt. Inverse modelling, sensitivity and monte carlo analysis in R using package FME. *Journal of Statistical Software*, 33(3):1–28, 2010. URL <http://www.jstatsoft.org/v33/i03/>.